



50PZA12M6.3X8 Information

Heisener.com

Part Number 50PZA12M6.3X8

Manufacturer Rubycon
Category Capacitors

Aluminum - Polymer Capacitors

Description CAP ALUM POLY 12UF 20% 50V T/H

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50PZA12M6.3X8 Specifications

Manufacturer Part Number 50PZA12M6.3X8 Manufacturer Rubycon Category Capacitors Package Radial, Can Series PZA Type Polymer Capacitance 12μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum - Polymer Capacitors Package Radial, Can Series PZA Type Polymer Capacitance 12µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	50PZA12M6.3X8
Package Radial, Can Series PZA Type Polymer Capacitance 12μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Rubycon
Package Radial, Can Series PZA Type Polymer Capacitance 12µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series PZA Type Polymer Capacitance 12µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum - Polymer Capacitors
Type Polymer Capacitance 12μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Capacitance $12\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. $3000 \text{ Hrs @ } 105^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 105^{\circ}C$ ApplicationsAutomotiveRipple Current - Low Frequency $40\text{mA @ } 120\text{Hz}$ Ripple Current - High Frequency $800\text{mA @ } 100\text{kHz}$ Impedance-Lead Spacing $0.098''$ (2.50mm)Size / Dimension $0.248''$ Dia (6.30mm)Height - Seated (Max) $0.374''$ (9.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Series	PZA
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Туре	Polymer
Voltage - Rated 50V ESR (Equivalent Series Resistance) 81 mOhm Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Capacitance	12μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 800mA @ 120Hz Rippedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 800mA @ 120Hz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	50V
Operating Temperature Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 800mA @ 120Hz 800mA @ 100kHz Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	81 mOhm
Applications Ripple Current - Low Frequency A0mA @ 120Hz Ripple Current - High Frequency RoomA @ 100kHz - Lead Spacing D.098" (2.50mm) Size / Dimension D.248" Dia (6.30mm) Height - Seated (Max) D.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	3000 Hrs @ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Current - Low Frequency Roman @ 120Hz Roman @ 100kHz - Lead Spacing - 0.098" (2.50mm) Size / Dimension - 0.248" Dia (6.30mm) Height - Seated (Max) - 0.374" (9.50mm) Surface Mount Land Size - Mounting Type - Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - High Frequency Impedance Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	40mA @ 120Hz
Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	800mA @ 100kHz
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.374" (9.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.374" (9.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

50PZA12M6.3X8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50PZA12M6.3X8 Payment Methods





















50PZA12M6.3X8 Shipping Methods













If you have any question about 50PZA12M6.3X8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com