



50RX3022M5X11 Information

Heisener.com

Part Number 50RX3022M5X11

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50RX3022M5X11 Specifications

Manufacturer Part Number 50RX3022M5X11 Manufacturer Rubycon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series RX30 Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lord Service -	ı	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series RX30 Capacitance 22μF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance	Manufacturer Part Number	50RX3022M5X11
Aluminum Electrolytic Capacitors Package Radial, Can Series RX30 Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Automotive Rippde Current - High Frequency Impedance Automotive Impedance Automotive Impedance Automotive Impedance Impedance Automotive Impedance Impedance Automotive Impedance Automotive Impedance Automotive Impedance Automotive Impedance	Manufacturer	Rubycon
PackageRadial, CanSeriesRX30Capacitance $22μF$ Tolerance $±20%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $1000 \text{ Hrs } @ 130^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 130^{\circ}\text{C}$ PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-	Category	Capacitors
Series RX30 Capacitance 22 μ F Tolerance $\pm 20\%$ Voltage - Rated ± 50 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. $1000 \text{ Hrs } @ 130^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 130^{\circ}\text{C}$ Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -		Aluminum Electrolytic Capacitors
Capacitance $22μF$ Tolerance $\pm 20\%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $1000 \text{ Hrs } @ 130^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 130^{\circ}\text{C}$ PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Series	RX30
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance - -	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 130°C Operating Temperature -40°C ~ 130°C Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Voltage - Rated	50V
Operating Temperature -40°C ~ 130°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance -40°C ~ 130°C Polar Automotive - - - - - - - - - - - - -	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Lifetime @ Temp.	1000 Hrs @ 130°C
Applications Automotive Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Operating Temperature	-40°C ~ 130°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance -	Polarization	Polar
Ripple Current - High Frequency - Impedance -	Applications	Automotive
Impedance -	Ripple Current - Low Frequency	-
-	Ripple Current - High Frequency	-
0.070" (2.00)	Impedance	-
Lead Spacing 0.079 (2.00mm)	Lead Spacing	0.079" (2.00mm)
Size / Dimension 0.197" Dia (5.00mm)	Size / Dimension	0.197" Dia (5.00mm)
Height - Seated (Max) 0.512" (13.00mm)	Height - Seated (Max)	0.512" (13.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report error		Report errors?

50RX3022M5X11 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50RX3022M5X11 Payment Methods


































If you have any question about 50RX3022M5X11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com