

Heisener.com

50WXA470MEFCG412.5X16

50WXA470MEFCG412.5X16 Information

Part Number 50WXA470MEFCG412.5X16

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50WXA470MEFCG412.5X16 Specifications

Manufacturer Part Number50WXA470MEFCG412.5X16ManufacturerRubyconCategoryCapacitorsPackageRadial, CanSeriesWXACapacitance470µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency570mA @ 120HzRipple Current - High Frequency684mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.689" (17.50mm)	*	
Category Capacitors Package Radial, Can Series WXA Capacitance 470µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Manufacturer Part Number	50WXA470MEFCG412.5X16
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesWXACapacitance470μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency570mA @ 120HzRipple Current - High Frequency684mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.689" (17.50mm)	Manufacturer	Rubycon
Package Radial, Can Series WXA Capacitance 470μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Category	Capacitors
Series WXA Capacitance 470μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Series	WXA
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) - 0.689" (17.50mm)	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Voltage - Rated	50V
Operating Temperature -55°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Frequency Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency Frequ	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency 570mA @ 120Hz Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Polarization	Polar
Ripple Current - High Frequency 684mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Ripple Current - Low Frequency	570mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Ripple Current - High Frequency	684mA @ 10kHz
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.689" (17.50mm)	Impedance	-
Height - Seated (Max) 0.689" (17.50mm)	Lead Spacing	0.197" (5.00mm)
-	Size / Dimension	0.492" Dia (12.50mm)
Surface Mount Land Size	Height - Seated (Max)	0.689" (17.50mm)
Surface Mount Edite Size	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

50WXA470MEFCG412.5X16 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50WXA470MEFCG412.5X16 Payment Methods



















50WXA470MEFCG412.5X16 Shipping Methods













If you have any question about 50WXA470MEFCG412.5X16, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com