

510-83-084-10-031101

510-83-084-10-031101 Information

Heisener.com	Part Number Manufacturer Category Description Package	510-83-084-10-031101 Preci-Dip Connectors, Interconnects Sockets for ICs, Transistors CONN SOCKET PGA 84POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



510-83-084-10-031101 Specifications

Manufacturer Preci-Dip Connectors, Interconnects Sockets for ICs, Transistors Package - Series 510 Species 510 Pype PGA Number of Positions or Pins (Grid) 84 (10 x 10) Pitch - Mating 0.100° (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating Gold Contact Finish - Mating Beryllium Copper Contact Material - Mating Beryllium Copper Contact Material - Mating Open Frame Pitch - Post Olo0° (2.54mm) Contact Finish - Post Solder Contact Finish - Post Open Frame Contact Finish - Post Olo0° (2.54mm) Contact Finish - Post Olo0° (2.54mm) Contact Finish - Post Solder Contact Finish Thickness - Post - Contact Material - Post Brass Contact Materi	_		
Category Connectors, Interconnects Sockets for ICs, Transistors Package - Series 510 Pype PGA Number of Positions or Pins (Grid) 84 (10 x 10) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating 29.5µin (0.75µm) Contact Finish Thickness - Mating 29.5µin (0.75µm) Contact Material - Mating Beryllium Copper Contact Material - Mating Solder Pitch - Post Open Frame Contact Finish - Post Solder Contact Finish Thickness - Post - Contact Material - Post Brass Contact Material - Post Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Deperating Temperature	Manufacturer Part Number	510-83-084-10-031101	
Sockets for ICs, TransistorsPackage-Series510SpeedPGANumber of Positions or Pins (Grid)84 (10 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating29.5µin (0.75µm)Contact Finish Thickness - MatingBeryllium CopperContact Material - MatingBeryllium CopperPackageOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Nating9.5µin (0.75µm)Contact Material - MatingBeryllium CopperContact Material - MatingBeryllium CopperContact Material - MatingSolderContact Finish Thickness - MatingSolderContact Finish - Post1inContact Finish - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer	Preci-Dip	
Package-Series510StypeGANumber of Positions or Pins (Grid)84 (10 x 10Pitch - Mating0.100° (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating9.5µin (0.75µm)Contact Material - MatingBeryllium CopperContact Material - MatingOne FrameFeaturesOpen FrameFerminationSolderContact Finish Thickness - Post1.00° (2.54mm)FerminationSolderContact Finish - Post0.100° (2.54mm)Contact Finish - Post5.0 colderContact Finish - Post1.00° (2.54mm)Contact Finish - Post5.0 colderContact Finish - Post5.0 colderContact Finish - Post5.0 colderContact Finish - Post5.0 colderContact Finish - Post5.0 colders/tenethylene Terephthalter (PCT), Polyester, Glass FilledContact Material - Post5.0° c 125°C	Category	Connectors, Interconnects	
Series 510 Fype PGA Number of Positions or Pins (Grid) 84 (10 x 10) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating 29.5µin (0.75µm) Contact Finish Thickness - Mating 29.5µin (0.75µm) Contact Material - Mating Beryllium Copper Contact Material - Mating Beryllium Copper Contact Material - Mating Depen Frame Poentrantion Solder Pertures 0.100" (2.54mm) Contact Finish - Post 0.100" (2.54mm) Contact Finish - Post Solder Contact Finish - Post Tin Contact Finish Thickness - Post - Contact Finish Thickness - Post - Contact Finish Thickness - Post - Contact Material - Post Brass Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Poperating Temperature -55°C ~ 125°C		Sockets for ICs, Transistors	
Fype PGA Number of Positions or Pins (Grid) 84 (10 x 10) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating 29.5µin (0.75µm) Contact Finish Thickness - Mating Beryllum Copper Contact Material - Mating Beryllum Copper Mounting Type Through Hole Features Open Frame Pitch - Post 0.100" (2.54mm) Contact Finish Thickness - Post 0.100" (2.54mm) Contact Finish - Post 0.100" (2.54mm) Contact Finish - Post 0.100" (2.54mm) Contact Finish Thickness - Post 5.010" Contact Finish - Post Solder Contact Finish Thickness - Post Final Contact Finish Thickness - Post - Contact Material - Post Sass Contact Material - Post Brass Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Depending Temperature 55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)84 (10 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleContact Material - MatingOpen FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Series	510	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - PostSiloerContact Finish - PostSolderContact Finish - PostFininContact Finish - PostSiloerContact Finish - PostSiloerContact Finish Thickness - PostSiloerContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledPoperating Temperature55°C ~ 125°C	Туре	PGA	
Contact Finish - MatingGoldContact Finish Thickness - Mating29.5µin (0.75µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleMounting TypeOpen FrameFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish Thickness - Post-Contact Finish Thickness - PostPitch - PostContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	84 (10 x 10)	
Contact Finish Thickness - Mating29.5µin (0.75µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish Thickness - Post-Contact Tinish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Housing Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled	Contact Finish Thickness - Mating	29.5µin (0.75µm)	
FeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish Thickness - Post-Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledPoperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
FerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Features	Open Frame	
Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	-	
$-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material - Post	Brass	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled	
Report errors?	Operating Temperature	-55°C ~ 125°C	
		Report errors?	

510-83-084-10-031101 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

510-83-084-10-031101 Payment Methods





If you have any question about 510-83-084-10-031101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com