



510D337M6R3CG3D Information

Heisener.com

Part Number 510D337M6R3CG3D Manufacturer Vishay Sprague Category

Capacitors

Aluminum Electrolytic Capacitors Description CAP ALUM 330UF 20% 6.3V RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









510D337M6R3CG3D Specifications

Manufacturer Part Number \$10D337M6R3CG3D Manufacturer Vishay Sprague Category Capacitors Package Radial, Can Series \$10D Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	•	
Category Capacitors Package Radial, Can Series 510D Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	510D337M6R3CG3D
Package Radial, Can Series 510D Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Vishay Sprague
Package Radial, Can Series 510D Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series 510D Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	510D
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.200" (5.08mm)Size / Dimension0.414" Dia (10.52mm)Height - Seated (Max)0.945" (24.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	330μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 30.200" (5.08mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing O.200" (5.08mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C -40°C ~ 105°C -40°C	Voltage - Rated	6.3V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.200" (5.08mm) Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.200" (5.08mm)Size / Dimension0.414" Dia (10.52mm)Height - Seated (Max)0.945" (24.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.200" (5.08mm)Size / Dimension0.414" Dia (10.52mm)Height - Seated (Max)0.945" (24.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.414" Dia (10.52mm) Height - Seated (Max) 0.945" (24.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.200" (5.08mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.414" Dia (10.52mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.945" (24.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

510D337M6R3CG3D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

510D337M6R3CG3D Payment Methods



















510D337M6R3CG3D Shipping Methods













If you have any question about 510D337M6R3CG3D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com