

510DX337M025DG2D Information

Heisener.com

Part Number 510DX337M025DG2D

Manufacturer Vishay Sprague

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330UF 20% 25V RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









510DX337M025DG2D Specifications

Manufacturer Part Number510DX337M025DG2DManufacturerVishay SpragueCategoryCapacitorsPackageRadial, CanSeries510DXCapacitance330µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)442 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency661mA @ 120HzRipple Current - High Frequency927mA @ 40kHzImpedance202 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.905" (23.00mm)Surface Mount Land Size-	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series 510DX Capacitance 330µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 442 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 661mA @ 120Hz Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Manufacturer Part Number	510DX337M025DG2D
Aluminum Electrolytic Capacitors Package Radial, Can Series S10DX Capacitance 330µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 442 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 661mA @ 120Hz Ripple Current - High Frequency Pipple Current	Manufacturer	Vishay Sprague
PackageRadial, CanSeries510DXCapacitance330µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)442 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency661mA @ 120HzRipple Current - High Frequency927mA @ 40kHzImpedance202 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.905" (23.00mm)Surface Mount Land Size-	Category	Capacitors
Series 510DX Capacitance 330μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 442 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 661mA @ 120Hz Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)442 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency661mA @ 120HzRipple Current - High Frequency927mA @ 40kHzImpedance202 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.905" (23.00mm)Surface Mount Land Size-	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 442 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 661mA @ 120Hz Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Series	510DX
Voltage - Rated ESR (Equivalent Series Resistance) 442 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 661mA @ 120Hz Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Capacitance	330μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Voltage - Rated	25V
Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Ripple Current - High Frequency Polar Size / Dimension Height - Seated (Max) Surface Mount Land Size -40°C ~ 125°C Polar Polar -40°C ~ 125°C Polar Polar Polar Polar Seneral Purpose 661mA @ 120Hz 927mA @ 40kHz 927mA @ 40kHz 1019mpedance 202 mOhms 0.197" (5.00mm) 0.995" (23.00mm)	ESR (Equivalent Series Resistance)	442 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 661mA @ 120Hz Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Lifetime @ Temp.	2000 Hrs @ 125°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Page 202 mOhms Lead Spacing Current - Dimension Output Dimensio	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency 927mA @ 40kHz Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Applications	General Purpose
Impedance 202 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	661mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	927mA @ 40kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.905" (23.00mm)Surface Mount Land Size-	Impedance	202 mOhms
Height - Seated (Max) 0.905" (23.00mm) Surface Mount Land Size -	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -	Size / Dimension	0.492" Dia (12.50mm)
	Height - Seated (Max)	0.905" (23.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

510DX337M025DG2D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

510DX337M025DG2D Payment Methods



















510DX337M025DG2D Shipping Methods













If you have any question about 510DX337M025DG2D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com