



510GCB-BAAG Information



For Reference Only

Part Number 510GCB-BAAG Manufacturer Silicon Labs

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG CMOS 2.5V EN/DS 20PPM

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









510GCB-BAAG Specifications

Manufacturer Part Number \$10GCB-BAAG Manufacturer Silicon Labs Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series Si510 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 125MHz ~ 169.999MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276° L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)			
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series Si510 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 125MHz ~ 169.999MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature 40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Manufacturer Part Number	510GCB-BAAG	
Package 6-SMD, No Lead Series Si510 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 125MHz ~ 169.999MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Manufacturer	Silicon Labs	
Package 6-SMD, No Lead Series Si510 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 125MHz ~ 169.999MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Category	Crystals, Oscillators, Resonators	
Series Si510 Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 125MHz ~ 169.999MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)		Programmable Oscillators	
TypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range125MHz ~ 169.999MHzFunctionEnable/DisableOutputCMOSVoltage - Supply2.5VFrequency Stability±20ppmFrequency Stability (Total)±30ppmOperating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)26mARatings-Mounting TypeSurface MountPackage / Case6-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.071" (1.80mm)	Package	6-SMD, No Lead	
Programmable Type Available Frequency Range 125MHz ~ 169.999MHz Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) 5pread Spectrum Bandwidth - Current - Supply (Max) Camba Ratings - Mounting Type Surface Mount Package / Case Size / Dimension 0.071" (1.80mm)	Series	Si510	
Available Frequency Range Function Enable/Disable Output CMOS Voltage - Supply 2.5V Frequency Stability +20ppm Frequency Stability (Total) 5pread Spectrum Bandwidth -Current - Supply (Max) Ratings -Mounting Type Surface Mount Package / Case Size / Dimension 0.071" (1.80mm) Enable/Disable E	Туре	XO (Standard)	
Function Enable/Disable Output CMOS Voltage - Supply 2.5 V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.00000000000000000000000000000000000	Programmable Type	Programmed as Request	
Output CMOS Voltage - Supply 2.5V Frequency Stability ±20ppm Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.0011 (1.80mm)	Available Frequency Range	125MHz ~ 169.999MHz	
Voltage - Supply Frequency Stability £20ppm Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case Size / Dimension 0.071" (1.80mm)	Function	Enable/Disable	
Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Output	CMOS	
Frequency Stability (Total) ±30ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Voltage - Supply	2.5V	
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Frequency Stability	±20ppm	
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Frequency Stability (Total)	±30ppm	
Current - Supply (Max) 26mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Operating Temperature	-40°C ~ 85°C	
Ratings Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Spread Spectrum Bandwidth	-	
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Current - Supply (Max)	26mA	
Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Ratings	-	
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Mounting Type	Surface Mount	
Height 0.071" (1.80mm)	Package / Case	6-SMD, No Lead	
-	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)	
Report errors?	Height	0.071" (1.80mm)	
•			Report errors?

510GCB-BAAG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

510GCB-BAAG Payment Methods



















510GCB-BAAG Shipping Methods













If you have any question about 510GCB-BAAG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com