



#### 5239WAB16X404 Information

Heisener.com

Part Number 5239WAB16X404

Manufacturer APEM Inc.
Category Switches

**Toggle Switches** 

**Description** SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 5239WAB16X404 Specifications

Manufacturer Part Number         5239WAB16X404           Manufacturer         APEM Inc.           Category         Switches           Package         -           Series         5000           Circuit         SPDT           Switch Function         On-Off-On           Current Rating         6A (AC), 4A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Standard Round           Actuator Length         7.30mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Through Hole, Right Angle           Termination Style         PC Pin           Panel Cutout Dimensions         -           Bushing Thread         Unthreaded           Ingress Protection         -           Features         Epoxy Sealed Terminals		
CategorySwitchesPackage-Series5000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length7.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	5239WAB16X404
Package - Series 5000 Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 7.30mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Monthing Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Sundard Round - Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer	APEM Inc.
Package-Series5000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length7.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series5000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length7.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length7.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length7.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Series	5000
Current Rating 6A (AC), 4A (DC)  Voltage Rating - AC 125V  Voltage Rating - DC 30V  Actuator Type Standard Round  Actuator Length 7.30mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Through Hole, Right Angle  Termination Style PC Pin  Panel Cutout Dimensions -  Bushing Thread Unthreaded  Ingress Protection -  Features Epoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length7.30mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 7.30mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC), 4A (DC)
Actuator Type Standard Round Actuator Length 7.30mm  Illumination Non-Illuminated  Illumination Type, Color Illumination Voltage (Nominal)  Mounting Type Through Hole, Right Angle Termination Style PC Pin  Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features  Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length 7.30mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal)  Mounting Type Through Hole, Right Angle  Termination Style PC Pin  Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Sushing Thread Unthreaded Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	7.30mm
Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin  Panel Cutout Dimensions -  Bushing Thread Unthreaded  Ingress Protection -  Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### 5239WAB16X404 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 5239WAB16X404 Payment Methods





















## 5239WAB16X404 Shipping Methods













If you have any question about 5239WAB16X404, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com