

### **52418-1410 Information**

Heisener.com

For Reference Only

**Part Number** 52418-1410

ManufacturerMolex Connector CorporationCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** CONN RECEPT RT ANG 14POS 2MM

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **52418-1410 Specifications**

Manufacturer Part Number  Manufacturer  Molex Connector Corporation  Category  Connectors, Interconnects  Rectangular Connectors - Headers, Receptacles, Female Sockets  Package  - Series  52418  Connector Type  Receptacle  Contact Type  Female Socket  Style  Board to Board  Number of Positions  14  Number of Positions Loaded  Pitch - Mating  Number of Rows  1  Row Spacing - Mating  Maunting Type  Through Hole Right Angle		
Category  Connectors, Interconnects  Rectangular Connectors - Headers, Receptacles, Female Sockets  Package  Series  52418  Connector Type  Receptacle  Contact Type  Female Socket  Style  Board to Board  Number of Positions  14  Number of Positions Loaded  Pitch - Mating  0.079" (2.00mm)  Number of Rows  1  Row Spacing - Mating  -	Manufacturer Part Number	52418-1410
Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series 52418 Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 14 Number of Positions Loaded Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating -	Manufacturer	Molex Connector Corporation
Package - Series 52418  Connector Type Receptacle Contact Type Female Socket Style Board to Board  Number of Positions 14  Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm)  Number of Rows 1  Row Spacing - Mating -	Category	Connectors, Interconnects
Series 52418  Connector Type Receptacle  Contact Type Female Socket  Style Board to Board  Number of Positions 14  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 1  Row Spacing - Mating -		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle  Contact Type Female Socket  Style Board to Board  Number of Positions 14  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 1  Row Spacing - Mating -	Package	-
Contact Type Female Socket  Style Board to Board  Number of Positions 14  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 1  Row Spacing - Mating -	Series	52418
Style Board to Board  Number of Positions 14  Number of Positions Loaded All  Pitch - Mating 0.079" (2.00mm)  Number of Rows 1  Row Spacing - Mating -	Connector Type	Receptacle
Number of Positions14Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-	Contact Type	Female Socket
Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating -	Style	Board to Board
Pitch - Mating 0.079" (2.00mm)  Number of Rows 1  Row Spacing - Mating -	Number of Positions	14
Number of Rows 1 Row Spacing - Mating -	Number of Positions Loaded	All
Row Spacing - Mating -	Pitch - Mating	0.079" (2.00mm)
	Number of Rows	1
Mounting Type Through Hole Pight Angle	Row Spacing - Mating	-
Mounting Type Tillough Hole, Night Angle	Mounting Type	Through Hole, Right Angle
Termination Press-Fit, Solder	Termination	Press-Fit, Solder
Fastening Type Friction Lock	Fastening Type	Friction Lock
Contact Finish - Mating Tin	Contact Finish - Mating	Tin
Contact Finish Thickness - Mating -	Contact Finish Thickness - Mating	-
Insulation Color Natural	Insulation Color	Natural
Insulation Height 0.124" (3.14mm)	Insulation Height	0.124" (3.14mm)
Contact Length - Post 0.126" (3.20mm)	Contact Length - Post	0.126" (3.20mm)
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### **52418-1410 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 52418-1410 Payment Methods



















## 52418-1410 Shipping Methods













If you have any question about 52418-1410, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com