

5280-6SG-315

equest a Quote

5280-6SG-315 Information

| Heisener.com | Part Number | 5280-6SG-315 |
|--------------------|--------------|---|
| | Manufacturer | Conxall/Switchcraft |
| | Category | Connectors, Interconnects Circular Connectors |
| | Description | CONN RCPT 6POS INLINE SKT |
| | Package | - |
| | | For the pricing/inventory/lead time, please contact |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5280-6SG-315 Specifications

| TerminationCrimpFastening TypeBayonet Lock | | |
|--|--------------------------|----------------------------|
| Category Connectors, Interconnects Circular Connectors Package - Series Multi-Con-X? Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Contact Finish Sold Contact Finish Gold Patures Backshell Voltage - Rated GolV Current Rating GolV | Manufacturer Part Number | 5280-6SG-315 |
| Circular ConnectorsPackage-SeriesMulti-Con-X?Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWathertightShell Material, FinishSoldContact FinishGoldFastensBackshellYoltage - Rated600VCurrent Rating-Current Rating-Statens- <td>Manufacturer</td> <td>Conxall/Switchcraft</td> | Manufacturer | Conxall/Switchcraft |
| Package-SeriesMult-Con-X?Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mouting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeydetIngress ProtectionWathertightShell Material, FinishSoldContact FinishGoldFasteningBayonet ContactYoltage - RatedBackshellYoltage - RatedBoloYoltage - RatedGoloYoltage - RatedGoloYoltage - RatedSoloYoltage - RatedYoltage - Yoltage - Yoltage - Yoltage - Yoltage - Yoltage - Yoltage - | Category | Connectors, Interconnects |
| SeriesMulti-Con-X?Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFasteningBackshellVoltage - Rated60VCurrent Rating- | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishGoldContact FinishGoldVoltage - RatedBackshellVoltage - Rated600VCurrent Rating-Current Rating- | Package | - |
| Number of Positions6Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Series | Multi-Con-X? |
| Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating-Shell Material, FinishSouth StatementShell StatementSouth StatementStatementSouth StatementStat | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Number of Positions | 6 |
| Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Shell Size - Insert | - |
| TerminationCrimpFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Shell Size, MIL | - |
| Fastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Mounting Type | Free Hanging (In-Line) |
| OrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Termination | Crimp |
| Ingress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Fastening Type | Bayonet Lock |
| Shell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Orientation | Keyed |
| Contact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Ingress Protection | Weathertight |
| FeaturesBackshellVoltage - Rated600VCurrent Rating- | Shell Material, Finish | Nylon |
| Voltage - Rated600VCurrent Rating- | Contact Finish | Gold |
| Current Rating - | Features | Backshell |
| - | Voltage - Rated | 600V |
| Report errors? | Current Rating | - |
| • | | Report errors? |

5280-6SG-315 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

5280-6SG-315 Payment Methods



5280-6SG-315 Shipping Methods



If you have any question about 5280-6SG-315, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com