



53D282G030JJ7 Information

Ma Ca Heisener.com

Part Number 53D282G030JJ7
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2800UF 30V AXIAL

Package Axial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









53D282G030JJ7 Specifications

Manufacturer Part Number 53D282G030J17 Manufacturer Vishay Sprague Category Capacitors Aluminum Electrolytic Capacitors Package Axial, Can Series 53D Capacitance 2800µF Tolerance 10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Elfetime @ Temp. 1000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can Report errors?			
Category Capacitors Aluminum Electrolytic Capacitors Package Axial, Can Series 53D Capacitance 2800µF Tolerance -10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer Part Number	53D282G030JJ7	
Aluminum Electrolytic Capacitors Package Axial, Can Series 53D Capacitance 2800µF Tolerance -10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer	Vishay Sprague	
Package Axial, Can Series 53D Capacitance 2800µF Tolerance -10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Category	Capacitors	
Series 53D Capacitance 2800µF Tolerance -10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can		Aluminum Electrolytic Capacitors	
Capacitance 2800µF Tolerance -10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Package	Axial, Can	
Tolerance -10%, +75% Voltage - Rated 30V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Assistance -	Series	53D	
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case - 1000 Hrs @ 85°C - 40°C ~ 85°C - General Purpose - - - - - - - - - - - - -	Capacitance	2800μF	
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Tolerance	-10%, +75%	
Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Voltage - Rated	30V	
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	-	
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C	
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Operating Temperature	-40°C ~ 85°C	
Ripple Current - Low Frequency	Polarization	Polar	
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Applications	General Purpose	
Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - Low Frequency	-	
Lead Spacing - Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - High Frequency	-	
Size / Dimension 1.012" Dia x 1.642" L (25.70mm x 41.70mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Impedance	-	
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Lead Spacing	-	
Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Size / Dimension	1.012" Dia x 1.642" L (25.70mm x 41.70mm)	
Mounting Type Through Hole Package / Case Axial, Can	Height - Seated (Max)	-	
Package / Case Axial, Can	Surface Mount Land Size	-	
-	Mounting Type	Through Hole	
Report errors?	Package / Case	Axial, Can	
			Report errors?

53D282G030JJ7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

53D282G030JJ7 Payment Methods



















53D282G030JJ7 Shipping Methods













If you have any question about 53D282G030JJ7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com