



53D402F063JP6 Information

Heisener.com

For Reference Only

Part Number 53D402F063JP6
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 4000UF 63V AXIAL

Package Axial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









53D402F063JP6 Specifications

Manufacturer Part Number 53D402F063JP6 Manufacturer Vishay Sprague Category Capacitors Package Axial, Can Series 53D Capacitance 4000µF Tolerance -10%, +50% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can Report errors?	•	
Category Capacitors Package Axial, Can Series 53D Capacitance 4000μF Tolerance -10%, +50% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Manufacturer Part Number	53D402F063JP6
PackageAluminum Electrolytic CapacitorsPackageAxial, CanSeries53DCapacitance4000μFTolerance-10%, +50%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension1.012" Dia x 2.642" L (25.70mm x 67.10mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Manufacturer	Vishay Sprague
Package Axial, Can Series 53D Capacitance 4000μF Tolerance -10%, +50% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Category	Capacitors
Series 53D Capacitance 4000µF Tolerance -10%, +50% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can		Aluminum Electrolytic Capacitors
Capacitance 4000µF Tolerance -10%, +50% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Package	Axial, Can
Tolerance -10%, +50% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Assial, Can	Series	53D
Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Capacitance	4000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar 1000 Hrs @ 85°C -40°C ~ 85°C Folar General Purpose - - - - - - - - - - - - -	Voltage - Rated	63V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Package / Case General Purpose - General Purpose - 1.012" Dia x 2.642" L (25.70mm x 67.10mm) - Through Hole Package / Case Axial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Ripple Current - High Frequency	-
Size / Dimension 1.012" Dia x 2.642" L (25.70mm x 67.10mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Axial, Can	Lead Spacing	-
Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Size / Dimension	1.012" Dia x 2.642" L (25.70mm x 67.10mm)
Mounting Type Through Hole Package / Case Axial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

53D402F063JP6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

53D402F063JP6 Payment Methods



















53D402F063JP6 Shipping Methods













If you have any question about 53D402F063JP6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com