

54-00060 Information



For Reference Only

Part Number 54-00060

Manufacturer Tensility International Corp

Category Connectors, Interconnects
Barrel - Power Connectors

Description CONN PWR JACK 1X3.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









54-00060 Specifications

Manufacturer Part Number54-00060ManufacturerTensility International CorpCategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.00mm ID (0.039"), 3.50mm OD (0.138")Actual Diameter0.039" (1.00mm ID), 0.146" (3.70mm OD)Number of Positions/Contacts2 Conductors, 2 ContactsInternal Switch(s)Does Not Contain SwitchMounting TypePanel MountMounting FeatureBulkhead - Rear Side NutTerminationSolderShieldingUnshieldedFeaturesMounting HardwareInsulation Color-Voltage - Rated12VDCCurrent Rating4AReport errors?		
Category Canectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated L2VDC Current Rating	Manufacturer Part Number	54-00060
Package - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Manufacturer	Tensility International Corp
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Package	-
Gender Male Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Series	-
Industry Recognized Mating Diameter 1.00mm ID (0.039"), 3.50mm OD (0.138") Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated 12VDC Current Rating 4A	Connector Type	Jack
Actual Diameter 0.039" (1.00mm ID), 0.146" (3.70mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Gender	Male
Number of Positions/Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated 12VDC Current Rating	Industry Recognized Mating Diameter	1.00mm ID (0.039"), 3.50mm OD (0.138")
Internal Switch(s) Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Unshielded Features Mounting Hardware Insulation Color Voltage - Rated Current Rating Does Not Contain Switch Panel Mount Bulkhead - Rear Side Nut Unshielded Lushielded Lushielded	Actual Diameter	0.039" (1.00mm ID), 0.146" (3.70mm OD)
Mounting TypePanel MountMounting FeatureBulkhead - Rear Side NutTerminationSolderShieldingUnshieldedFeaturesMounting HardwareInsulation Color-Voltage - Rated12VDCCurrent Rating4A	Number of Positions/Contacts	2 Conductors, 2 Contacts
Mounting Feature Bulkhead - Rear Side Nut Termination Solder Unshielded Features Mounting Hardware Insulation Color Voltage - Rated Current Rating Bulkhead - Rear Side Nut Analysis Side Nut Local Solder Local So	Internal Switch(s)	Does Not Contain Switch
Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Mounting Type	Panel Mount
Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Mounting Feature	Bulkhead - Rear Side Nut
Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 4A	Termination	Solder
Insulation Color Voltage - Rated 12VDC Current Rating 4A	Shielding	Unshielded
Voltage - Rated 12VDC Current Rating 4A	Features	Mounting Hardware
Current Rating 4A	Insulation Color	-
	Voltage - Rated	12VDC
Report errors?	Current Rating	4A
		Report errors

54-00060 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

54-00060 Payment Methods



















54-00060 Shipping Methods













If you have any question about 54-00060, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com