

54-00062 Information

Part Number 54-00062

Manufacturer Tensility International Corp

Category Connectors, Interconnects
Barrel - Power Connectors

Description CONN PWR JACK 1.7X4.75MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









54-00062 Specifications

Manufacturer Part Number54-00062ManufacturerTensility International CorpCategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3Actual Diameter0.065" (1.65mm ID), 0.195" (4.95mm OD)Number of Positions/Contacts2 Conductors, 2 ContactsInternal Switch(s)Does Not Contain SwitchMounting TypePanel MountMounting FeatureBulkhead - Rear Side NutTerminationSolderShieldingUnshieldedFeaturesMounting HardwareInsulation Color-Voltage - Rated12VDCCurrent Rating5A			
Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3 Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 1 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated 12VDC Current Rating Connectors, Interconnects Barrel - Power Connectors Level - Power Con	Manufacturer Part Number	54-00062	
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3 Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A	Manufacturer	Tensility International Corp	
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3 Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A	Category	Connectors, Interconnects	
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3 Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A		Barrel - Power Connectors	
Connector Type Gender Male Industry Recognized Mating Diameter 1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3 Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated 12VDC Current Rating 5 A	Package	-	
GenderMaleIndustry Recognized Mating Diameter1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3Actual Diameter0.065" (1.65mm ID), 0.195" (4.95mm OD)Number of Positions/Contacts2 Conductors, 2 ContactsInternal Switch(s)Does Not Contain SwitchMounting TypePanel MountMounting FeatureBulkhead - Rear Side NutTerminationSolderShieldingUnshieldedFeaturesMounting HardwareInsulation Color-Voltage - Rated12VDCCurrent Rating5A	Series	-	
Industry Recognized Mating Diameter 1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3 Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated 12VDC Current Rating 5 A	Connector Type	Jack	
Actual Diameter 0.065" (1.65mm ID), 0.195" (4.95mm OD) Number of Positions/Contacts 2 Conductors, 2 Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A	Gender	Male	
Number of Positions/Contacts Internal Switch(s) Does Not Contain Switch Mounting Type Panel Mount Bulkhead - Rear Side Nut Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color Voltage - Rated 12VDC Current Rating	Industry Recognized Mating Diameter	1.70mm ID (0.067"), 4.75mm OD (0.187") EIAJ-3	
Internal Switch(s) Mounting Type Panel Mount Mounting Feature Bulkhead - Rear Side Nut Termination Solder Unshielded Features Mounting Hardware Insulation Color Voltage - Rated Current Rating Does Not Contain Switch Bunkhead - Rear Side Nut Bulkhead - Rear Side Nut - Unshielded 12VDC 5A	Actual Diameter	0.065" (1.65mm ID), 0.195" (4.95mm OD)	
Mounting TypePanel MountMounting FeatureBulkhead - Rear Side NutTerminationSolderShieldingUnshieldedFeaturesMounting HardwareInsulation Color-Voltage - Rated12VDCCurrent Rating5A	Number of Positions/Contacts	2 Conductors, 2 Contacts	
Mounting Feature Bulkhead - Rear Side Nut Termination Solder Unshielded Features Mounting Hardware Insulation Color Voltage - Rated Current Rating Bulkhead - Rear Side Nut Muther Side Nut Line Side Nut L	Internal Switch(s)	Does Not Contain Switch	
Termination Solder Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A	Mounting Type	Panel Mount	
Shielding Unshielded Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A	Mounting Feature	Bulkhead - Rear Side Nut	
Features Mounting Hardware Insulation Color - Voltage - Rated 12VDC Current Rating 5A	Termination	Solder	
Insulation Color Voltage - Rated 12VDC Current Rating 5A	Shielding	Unshielded	
Voltage - Rated 12VDC Current Rating 5A	Features	Mounting Hardware	
Current Rating 5A	Insulation Color	-	
•	Voltage - Rated	12VDC	
Report errors?	Current Rating	5A	
			Report errors?

54-00062 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

54-00062 Payment Methods





















54-00062 Shipping Methods













If you have any question about 54-00062, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com