

55030R2BI5.5

lest a Quote

55030R2BI5.5 Information

Heisener.com	Part Number	55030R2BI5.5	
	Manufacturer	Littelfuse Inc.	
	Category	Circuit Protection Electrical, Specialty Fuses	
	Description	FUSE CARTRIDGE 550A 5.5KVAC CYL	
	Package	Cylindrical, Blade Terminal (Bolt)	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



55030R2BI5.5 Specifications

ManufacturerLittlefuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating550AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeGut MountPackage / CaseCylindrical, Blade Terminal (Bolt)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent RatingS50AVoltage Rating - ACS500V (5.5kV)Voltage Rating - DC-ApplicationsMotor ProtectionFuse TypeIndicatingCartridgeIndicatingPackageResponse TimePatteresRating - ACApplicationsStol ProtectionPatteresIndicatingClassRApprovals-Operating TemperatureSioNAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.00mm x 193.04mm)	Manufacturer Part Number	55030R2BI5.5
Bit ControlPackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating550AVoltage Rating - AC550OV (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating TemperatureS0kABreaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent RatingS50AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating TemperatureS0KABreaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mn x 76.20mn x 193.04mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating550AVoltage Rating - AC550OV (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature90ABreaking Capacity @ Rated Voltage80AAMounting TypeBol MountPackage / CaseSioNO' L x 3.000'' W x 7.600'' H (457.20mm x 193.04mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse TypeSofACurrent RatingSofOV (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating TemperatureSofABreaking Capacity @ Rated VoltageSofAMounting TypeBolt MountPackage / CaseCylindrical Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 193.04mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating550AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating TemperatureS0kABreaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Series	POWR-GARD?
Voltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Current Rating	550A
Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Voltage Rating - AC	5500V (5.5kV)
ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Voltage Rating - DC	-
IndicatingFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Response Time	-
ClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Applications	Motor Protection
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Class	R
Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Approvals	-
Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Operating Temperature	-
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	18.000" L x 3.000" W x 7.600" H (457.20mm x 76.20mm x 193.04mm)
		Report errors?

55030R2BI5.5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

55030R2BI5.5 Payment Methods



55030R2BI5.5 Shipping Methods



If you have any question about 55030R2BI5.5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com