

55508-150LF

55508-150LF Information

		55508-150LF Amphenol FCI Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN RECEPT 50POS 2MM STR DL SMD		
For Reference Only		For the pricing/inventory/lead time, please contact us	Elanation of	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



55508-150LF Specifications

Manufacturer Part Number55508-150LFManufacturerAmphenol FCICategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions LoadedAllNumber of Rossi2Rowspacing - Mating0/079" (2.00mm)Number of Rows2Rowspacing - MatingSolderMounting TypeSuface MountFerniationSolderContact Finish - MatingGoldContact Finish - MatingGoldStation ColorBlackStation ColorBlackStation Finish - MatingSolderContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingSini (0.76µm)Station ColorBlackStation ColorSini (2.30mm)Station Finish Thickness - MatingSini (2.30mm)Station Finish ThicknessSini (2.30mm)Station Finish ThicknessSini (2.30mm)Station Fini Fini Fini Fini (2.30mm)Sini (2.30mm)Station Fini Fini Fini (2.30mm)Sini (2.30mm)Station Fini (3.30mm)Sini (3.30m				
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows2Row Spacing - MatingSolderMounting TypeSurface MountFreminationSolderFastening TypeGuid O.0100000000000000000000000000000000000	Manufacturer Part Number	55508-150LF		
Package-SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of PositionsS0Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingSolderYouring TypeSurface MountYouring TypeSurface MountFastening TypeOldContact Finish - MatingGoldSolderSolderFastening TypeSurface MountContact Finish - MatingGoldContact Finish - MatingJupin (0.76µm)Sutation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Sortact Length - Post-Sortact Surg Temperature-Sortact Surg Temperature-	Manufacturer	Amphenol FCI		
Package-SeriesMintek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderTerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingJojin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Optenting Temperature55°C ~ 125°C	Category	Connectors, Interconnects		
SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderContact Finish - MatingSolderContact Finish - MatingGoldSundator ColorBiakaiInsulation ColorBiackInsulation Height0.091" (2.30mm)Contact Funge ForstSickSundator HeightSolerSundator HeightSolerSundator SolerSickSundation SolerSolerSundation ColorSickSundation HeightSolerSonger SolerSickSundation HeightSickSolerSickSolerSickSolerSickSundation HeightSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSickSolerSick		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllNumber of Positions Loaded0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountForminationSolderContact Finish - MatingSolderContact Finish - MatingGoldIsulation ColorBiakIsulation Finish - MatingSolderIsulation Finish - MatingSolderContact Finish - MatingSolderIsulation Finish - MatingSolderIsolation Finish - M	Package	-		
Contact TypeFenale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Series	Minitek?		
StyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypeSolderContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post55°C ~ 125°C	Connector Type	Receptacle		
Number of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Sperating Temperature-Solder-	Contact Type	Female Socket		
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJoµin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Style	Board to Board		
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.091" (2.30mm)Contact Length - Post-55°C ~ 125°C	Number of Positions	50		
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All		
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)		
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Number of Rows	2		
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)		
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount		
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder		
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold		
Insulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)		
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black		
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.091" (2.30mm)		
	Contact Length - Post	-		
	Operating Temperature	-55°C ~ 125°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?



If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 55508-150LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com