



5550B103K802LE Information

Heisener.com

5550B103K802LE Part Number Manufacturer Knowles Novacap

Category Capacitors Ceramic Capacitors

Description CAP RADIAL 5550,10NF,8KV,10%,X7R

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5550B103K802LE Specifications

Manufacturer Part Number 5550B103K802LE Manufacturer Knowles Novacap Category Capacitors Package Radial Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Spacing 0.580" (14.73mm) Report errors?		
Category Capacitors Package Radial Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Manufacturer Part Number	5550B103K802LE
Package Radial Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Manufacturer	Knowles Novacap
Package Radial Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Category	Capacitors
Series - Capacitance 10000pF Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight		Ceramic Capacitors
Capacitance 10000pF Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Package	Radial
Tolerance ±10% Voltage - Rated 8000V (8kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Series	-
Voltage - Rated8000V (8kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.700" L x 0.402" W (17.78mm x 10.20mm)Height - Seated (Max)0.775" (19.68mm)Thickness (Max)-Lead Spacing0.580" (14.73mm)Lead StyleStraight	Capacitance	10000pF
Temperature Coefficient AyrR Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Thickness (Max) Lead Spacing Lead Style X7R AyrR AyrR - Lead Syneing General Purpose General Purpose Failure Rate - 0 General Purpose - 0 General P	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.700" L x 0.402" W (17.78mm x 10.20mm)Height - Seated (Max)0.775" (19.68mm)Thickness (Max)-Lead Spacing0.580" (14.73mm)Lead StyleStraight	Voltage - Rated	8000V (8kV)
Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Features	High Voltage
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.700" L x 0.402" W (17.78mm x 10.20mm)Height - Seated (Max)0.775" (19.68mm)Thickness (Max)-Lead Spacing0.580" (14.73mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.700" L x 0.402" W (17.78mm x 10.20mm) Height - Seated (Max) 0.775" (19.68mm) Thickness (Max) - Lead Spacing 0.580" (14.73mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style O.775" (19.68mm) - U.580" (14.73mm) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.580" (14.73mm) Lead Style Straight	Size / Dimension	0.700" L x 0.402" W (17.78mm x 10.20mm)
Lead Spacing0.580" (14.73mm)Lead StyleStraight	Height - Seated (Max)	0.775" (19.68mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.580" (14.73mm)
Report errors?	Lead Style	Straight
Report crisis:		Report errors?

5550B103K802LE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5550B103K802LE Payment Methods



















5550B103K802LE Shipping Methods













If you have any question about 5550B103K802LE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com