

Heisener.com

55639AVDEULCSA+U272

55639AVDEULCSA+U272 Information

Part Number 55639AVDEULCSA+U272

ManufacturerAPEM Inc.CategorySwitches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









55639AVDEULCSA+U272 Specifications

Manufacturer Part Number 55639AVDEULCSA+U272 Manufacturer APEM Inc. Category Switches Package - Series 55000 Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
Category Switches Package - Series 55000 Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer Part Number	55639AVDEULCSA+U272
Package - Series 55000 Circuit SPDT Switch Function On-Off-On Current Rating On-Off-On Current Rating - AC Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Solder Lug Panel Cutout Dimensions Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	APEM Inc.
Package - Series 55000 Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 55000 Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC) Voltage Rating - AC 125V Voltage Rating - DC - Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Termination Style Panel Mount Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard Round with CapActuator Length11.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating6A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard Round with CapActuator Length11.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	55000
Current Rating6A (AC)Voltage Rating - AC125 VVoltage Rating - DC-Actuator TypeStandard Round with CapActuator Length11.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC - Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Features Features Features Features Standard Round Non- Standard Round with Cap Standard R	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC)
Actuator Type Standard Round with Cap Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length 11.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	-
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Standard Round with Cap
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	11.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

55639AVDEULCSA+U272 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

55639AVDEULCSA+U272 Payment Methods





















55639AVDEULCSA+U272 Shipping Methods













If you have any question about 55639AVDEULCSA+U272, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com