

5580601003 Information

Heisener.com

Part Number 5580601003

Manufacturer Dialight

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED PANEL SNAP-IN YELLOW 592NM

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5580601003 Specifications

Manufacturer Part Number 5580601003 Manufacturer Dialight Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 558 Type LED Lamp Color Yellow Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features - Report errors?		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 558 Type LED Lamp Color Yellow Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Manufacturer Part Number	5580601003
Package - Series 558 Type LED Lamp Color Yellow Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features Features 558 CHD Current Colorless Clear Colorles Clear Colorles Clear Colorles Colorles Colorles Colorles Clear Colorles Colo	Manufacturer	Dialight
Package - Series 558 Type LED Lamp Color Yellow Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Category	Optoelectronics
Series 558 Type LED Lamp Color Yellow Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorYellowLens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak592nmViewing Angle45°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Ingress Protection - Features - Vellow Colorless Colorless Round Nax) Fellow None Clear Round Nax) Vi (Max) 1.9V Current 50mA Round Round Round Round Round Viewing Angle 45° Fermination Style Wire Leads - 6" (152.40mm) Features	Series	558
Lens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak592nmViewing Angle45°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Type	LED
Lens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak592nmViewing Angle45°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lamp Color	Yellow
Ratings Voltage 1.9V Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features -	Lens Color	Colorless
Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.16" (4.06mm)Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak592nmViewing Angle45°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lens Transparency	Clear
Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions 0.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Voltage	1.9V
Panel Cutout Dimensions O.16" (4.06mm) Lens Style/Size Round with Domed Top, 3mm (T-1) Millicandela Rating 200mcd Wavelength - Peak 592nm Viewing Angle 45° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection Features -	Current	50mA
Lens Style/SizeRound with Domed Top, 3mm (T-1)Millicandela Rating200mcdWavelength - Peak592nmViewing Angle45°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating Wavelength - Peak 592nm Viewing Angle Termination Style Ingress Protection Features 200mcd 592nm Wire Leads - 6" (152.40mm)	Panel Cutout Dimensions	0.16" (4.06mm)
Wavelength - Peak Viewing Angle 45° Termination Style Mire Leads - 6" (152.40mm) Ingress Protection Features -	Lens Style/Size	Round with Domed Top, 3mm (T-1)
Viewing Angle45°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Millicandela Rating	200mcd
Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Wavelength - Peak	592nm
Ingress Protection	Viewing Angle	45°
Features -	Termination Style	Wire Leads - 6" (152.40mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

5580601003 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5580601003 Payment Methods



















5580601003 Shipping Methods













If you have any question about 5580601003, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com