

5590302007F Information



For Reference Only

Part Number 5590302007F Manufacturer Dialight

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED SNAP-IN PANEL 5MM 5V YLW

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5590302007F Specifications

Manufacturer Part Number 5590302007F Manufacturer Dialight Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 559 Type LED Lamp Color Yellow Lens Color - Lens Transparency Diffused Ratings DC Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features - Report errors?		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 559 Type LED Lamp Color Yellow Lens Color - Lens Transparency Diffused Ratings DC Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Manufacturer Part Number	5590302007F
Package - Series 559 Type LED Lamp Color Yellow Lens Color - Lens Transparency Diffused Ratings DC Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Manufacturer	Dialight
Package - Series 559 Type LED Lamp Color Yellow Lens Color - Lens Transparency Diffused Ratings DC Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Category	Optoelectronics
Series 559 Type LED Lamp Color Yellow Lens Color - Lens Transparency Diffused Ratings DC Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorYellowLens Color-Lens TransparencyDiffusedRatingsDCVoltage5VCurrent12mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcdWavelength - Peak583nmViewing Angle60°Termination StyleWire Leads - 14" (355.60mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Lens Transparency Diffused Ratings DC Voltage SV Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating Wavelength - Peak S83nm Viewing Angle G0° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection Features Yellow Diffused For Current - Carpental Style SV Wire Leads - 14" (355.60mm) Features - Carpental SS Features Yellow Features DEM Termination Style SV Wire Leads - 14" (355.60mm) Features - Carpental SS Features Features	Series	559
Lens Color-Lens TransparencyDiffusedRatingsDCVoltage5VCurrent12mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcdWavelength - Peak583nmViewing Angle60°Termination StyleWire Leads - 14" (355.60mm)Ingress Protection-Features-	Type	LED
Lens TransparencyDiffusedRatingsDCVoltage5VCurrent12mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcdWavelength - Peak583nmViewing Angle60°Termination StyleWire Leads - 14" (355.60mm)Ingress Protection-Features-	Lamp Color	Yellow
Ratings DC Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection Features -	Lens Color	-
Voltage 5V Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Lens Transparency	Diffused
Current 12mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Ratings	DC
Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Voltage	5V
Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Current	12mA
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcdWavelength - Peak583nmViewing Angle60°Termination StyleWire Leads - 14" (355.60mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating8mcdWavelength - Peak583nmViewing Angle60°Termination StyleWire Leads - 14" (355.60mm)Ingress Protection-Features-	Panel Cutout Dimensions	0.25" (6.35mm)
Wavelength - Peak 583nm Viewing Angle 60° Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4)
Viewing Angle60°Termination StyleWire Leads - 14" (355.60mm)Ingress Protection-Features-	Millicandela Rating	8mcd
Termination Style Wire Leads - 14" (355.60mm) Ingress Protection - Features -	Wavelength - Peak	583nm
Ingress Protection Features	Viewing Angle	60°
Features -	Termination Style	Wire Leads - 14" (355.60mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

5590302007F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5590302007F Payment Methods



















5590302007F Shipping Methods













If you have any question about 5590302007F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com