

5593501808 Information

Heisener.com

Part Number 5593501808 Manufacturer Dialight

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED PANEL SNAP-IN BICLR RD/GN 3L

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5593501808 Specifications

Manufacturer Part Number 5593501808 Manufacturer Dialight Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 559 Type LED Lamp Color Green, Red Lens Color - Lens Transparency - Ratings Vf (Typ), If (Max) Voltage 2.3V Green, 2.1V Red Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features - Report errors?		
CategoryOptoelectronicsPackage-Series559TypeLEDLamp ColorGreen, RedLens Transparency-RatingsVf (Typ), If (Max)Voltage2.3V Green, 2.1V RedCurrent30mA Green, 30mA RedPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcd Green, 5mcd RedWavelength - Peak565nm Green, 635nm RedViewing Angle65°Termination Style-Ingress Protection-Features-	Manufacturer Part Number	5593501808
Package - Series 559 Type LED Lamp Color Green, Red Lens Transparency - Lens Transparency - Ratings Vf (Typ), If (Max) Voltage 2.3V Green, 2.1V Red Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 635nm Red Viewing Angle 65° Termination Style Ingress Protection - Features 559	Manufacturer	Dialight
Package-Series559TypeLEDLamp ColorGreen, RedLens Color-Lens Transparency-RatingsVf (Typ), If (Max)Voltage2.3V Green, 2.1V RedCurrent30mA Green, 30mA RedPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcd Green, 5mcd RedWavelength - Peak565nm Green, 635nm RedViewing Angle65°Termination Style-Ingress Protection-Features-	Category	Optoelectronics
Series 559 Type LED Lamp Color Green, Red Lens Color - Lens Transparency - Ratings Vf (Typ), If (Max) Voltage 2.3V Green, 2.1V Red Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorGreen, RedLens Color-Lens Transparency-RatingsVf (Typ), If (Max)Voltage2.3V Green, 2.1V RedCurrent30mA Green, 30mA RedPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcd Green, 5mcd RedWavelength - Peak565nm Green, 635nm RedViewing Angle65°Termination Style-Ingress Protection-Features-	Package	-
Lamp Color Lens Color Lens Transparency - Ratings Vf (Typ), If (Max) Voltage 2.3V Green, 2.1V Red Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak Viewing Angle 65° Termination Style Ingress Protection - Features - Green, Red	Series	559
Lens Color-Lens Transparency-RatingsVf (Typ), If (Max)Voltage2.3V Green, 2.1V RedCurrent30mA Green, 30mA RedPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcd Green, 5mcd RedWavelength - Peak565nm Green, 635nm RedViewing Angle65°Termination Style-Ingress Protection-Features-	Туре	LED
Lens Transparency-RatingsVf (Typ), If (Max)Voltage2.3V Green, 2.1V RedCurrent30mA Green, 30mA RedPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating8mcd Green, 5mcd RedWavelength - Peak565nm Green, 635nm RedViewing Angle65°Termination Style-Ingress Protection-Features-	Lamp Color	Green, Red
Ratings Voltage 2.3V Green, 2.1V Red Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style Ingress Protection - Features	Lens Color	-
Voltage 2.3V Green, 2.1V Red Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features -	Lens Transparency	-
Current 30mA Green, 30mA Red Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features -	Ratings	Vf (Typ), If (Max)
Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection Features - Round Round 6.35mm) - Round with Domed Top, 5mm (T-1 3/4) - Round Found Fou	Voltage	2.3V Green, 2.1V Red
Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style Ingress Protection - Features -	Current	30mA Green, 30mA Red
Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features -	Panel Cutout Shape	Round
Millicandela Rating 8mcd Green, 5mcd Red Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features -	Panel Cutout Dimensions	0.25" (6.35mm)
Wavelength - Peak 565nm Green, 635nm Red Viewing Angle 65° Termination Style - Ingress Protection - Features -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4)
Viewing Angle65°Termination Style-Ingress Protection-Features-	Millicandela Rating	8mcd Green, 5mcd Red
Termination Style - Ingress Protection - Features -	Wavelength - Peak	565nm Green, 635nm Red
Ingress Protection - Features -	Viewing Angle	65°
Features -	Termination Style	-
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

5593501808 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5593501808 Payment Methods



















5593501808 Shipping Methods













If you have any question about 5593501808, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com