

### **5596101023F Information**

Heisener.com

Part Number 5596101023F
Manufacturer Dialight

**Category** Optoelectronics

Panel Indicators, Pilot Lights

**Description** LED PMI SNAP-IN RED PVC FREE

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 5596101023F Specifications

Manufacturer         5596101023F           Manufacturer         Dialight           Category         Optoelectronics           Panel Indicators, Pilot Lights           Package         -           Series         559           Type         LED           Lamp Color         Red           Lens Color         Colorless           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         1.9V           Current         50mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.25" (6.35mm)           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4)           Millicandela Rating         2100mcd           Wavelength - Peak         635nm           Viewing Angle         50°           Termination Style         Wire Leads - 6" (152.40mm)           Ingress Protection         -           Features         -		
Category         Optoelectronics           Panel Indicators, Pilot Lights           Package         -           Series         559           Type         LED           Lamp Color         Red           Lens Color         Colorless           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         1.9V           Current         50mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.25" (6.35mm)           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4)           Millicandela Rating         2100mcd           Wavelength - Peak         635nm           Viewing Angle         50°           Termination Style         Wire Leads - 6" (152.40mm)           Ingress Protection         -           Features         -	Manufacturer Part Number	5596101023F
Package - Series 559 Type LED Lamp Color Red Lens Color Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 2100mcd Wavelength - Peak 635nm Viewing Angle 50° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features 6599	Manufacturer	Dialight
Package         -           Series         559           Type         LED           Lamp Color         Red           Lens Color         Colorless           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         1.9V           Current         50mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.25" (6.35mm)           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4)           Millicandela Rating         2100mcd           Wavelength - Peak         635nm           Viewing Angle         50°           Termination Style         Wire Leads - 6" (152.40mm)           Ingress Protection         -           Features         -	Category	Optoelectronics
Series         559           Type         LED           Lamp Color         Red           Lens Color         Colorless           Lens Transparency         Clear           Ratings         Vf (Typ), If (Max)           Voltage         1.9V           Current         50mA           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.25" (6.35mm)           Lens Style/Size         Round with Domed Top, 5mm (T-1 3/4)           Millicandela Rating         2100mcd           Wavelength - Peak         635nm           Viewing Angle         50°           Termination Style         Wire Leads - 6" (152.40mm)           Ingress Protection         -           Features         -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorRedLens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Package	-
Lamp Color Lens Color Colorless Lens Transparency Clear Ratings Vf (Typ), If (Max) Voltage 1.9V Current 50mA Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 2100mcd Wavelength - Peak 635nm Viewing Angle 50° Termination Style Ingress Protection - Features - Red Colorless Vf (Current Solorless Vi (Max) Voltage 1.9V Current 50mA Round Roun	Series	559
Lens ColorColorlessLens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Туре	LED
Lens TransparencyClearRatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lamp Color	Red
RatingsVf (Typ), If (Max)Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lens Color	Colorless
Voltage1.9VCurrent50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Lens Transparency	Clear
Current50mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.25" (6.35mm)Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Ratings	Vf (Typ), If (Max)
Panel Cutout Shape Round Panel Cutout Dimensions 0.25" (6.35mm) Lens Style/Size Round with Domed Top, 5mm (T-1 3/4) Millicandela Rating 2100mcd Wavelength - Peak 635nm Viewing Angle 50° Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Voltage	1.9V
Panel Cutout Dimensions  0.25" (6.35mm)  Lens Style/Size  Round with Domed Top, 5mm (T-1 3/4)  Millicandela Rating  2100mcd  Wavelength - Peak  635nm  Viewing Angle  50°  Termination Style  Wire Leads - 6" (152.40mm)  Ingress Protection  - Features  -	Current	50mA
Lens Style/SizeRound with Domed Top, 5mm (T-1 3/4)Millicandela Rating2100mcdWavelength - Peak635nmViewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Panel Cutout Shape	Round
Millicandela Rating  2100mcd  Wavelength - Peak  635nm  Viewing Angle  50°  Termination Style  Wire Leads - 6" (152.40mm)  Ingress Protection  Features  -	Panel Cutout Dimensions	0.25" (6.35mm)
Wavelength - Peak  Viewing Angle  50°  Termination Style  Wire Leads - 6" (152.40mm)  Ingress Protection  Features  -	Lens Style/Size	Round with Domed Top, 5mm (T-1 3/4)
Viewing Angle50°Termination StyleWire Leads - 6" (152.40mm)Ingress Protection-Features-	Millicandela Rating	2100mcd
Termination Style Wire Leads - 6" (152.40mm) Ingress Protection - Features -	Wavelength - Peak	635nm
Ingress Protection - Features -	Viewing Angle	50°
Features -	Termination Style	Wire Leads - 6" (152.40mm)
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

#### **5596101023F Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 5596101023F Payment Methods



















### 5596101023F Shipping Methods













If you have any question about 5596101023F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com