

### 5606175 Information



For Reference Only

Part Number 5606175

Manufacturer Phoenix Contact
Category RF/IF and RFID
RF Antennas

**Description** ZACK STRIP FLAT UNPRINTED

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 5606175 Specifications

Manufacturer Part Number         5606175           Manufacturer         Phoenix Contact           Category         RF/IF and RFID           REALAGE         RF Antennas           Package         -           Series         -           Frequency Group         UHF (300 MHz ~ 1 GHz)           Frequency Queter/Band)         900MHz           Frequency Range         890MHz ~ 960MHz           Antenna Type         Puck           Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         Report errors?	•	
Category         RF/IF and RFID           RF Antennas           Package         -           Series         -           Frequency Group         UHF (300 MHz ~ 1 GHz)           Frequency (Center/Band)         900MHz           Frequency Range         890MHz ~ 960MHz           Antenna Type         Puck           Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         -	Manufacturer Part Number	5606175
Package         -           Series         -           Frequency Group         UHF (300 MHz ~ 1 GHz)           Frequency (Center/Band)         900MHz           Frequency Range         890MHz ~ 960MHz           Antenna Type         Puck           Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         -	Manufacturer	Phoenix Contact
Package         -           Series         -           Frequency Group         UHF (300 MHz ~ 1 GHz)           Frequency (Center/Band)         900MHz           Frequency Range         890MHz ~ 960MHz           Antenna Type         Puck           Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         -	Category	RF/IF and RFID
Series         -           Frequency Group         UHF (300 MHz ~ 1 GHz)           Frequency (Center/Band)         900MHz           Frequency Range         890MHz ~ 960MHz           Antenna Type         Puck           Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         -		RF Antennas
Frequency Group Frequency (Center/Band) Frequency Range  890MHz ~ 960MHz  Antenna Type Puck  Number of Bands 1  VSWR - Return Loss - Gain 2.14dBi  Power - Max - Features - Termination Connector, N Male Ingress Protection Mounting Type Height (Max) Applications  UHF (300 MHz ~ 1 GHz) 900MHz  890MHz 900MHz 900M	Package	-
Frequency (Center/Band)         900MHz           Frequency Range         890MHz ~ 960MHz           Antenna Type         Puck           Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         -	Series	-
Frequency Range Antenna Type Puck  Number of Bands 1 VSWR - Return Loss - Gain 2.14dBi  Power - Max - Features - Termination Ingress Protection Mounting Type Panel Mount Height (Max) Applications  890MHz ~ 960MHz Puck  Puck  1 Connector, N Male 1.250" (31.75mm)  - Applications	Frequency Group	UHF (300 MHz ~ 1 GHz)
Antenna Type Puck Number of Bands 1  VSWR Return Loss Gain 2.14dBi  Power - Max Features Termination Connector, N Male Ingress Protection Mounting Type Panel Mount Height (Max) 1.250" (31.75mm) Applications	Frequency (Center/Band)	900MHz
Number of Bands         1           VSWR         -           Return Loss         -           Gain         2.14dBi           Power - Max         -           Features         -           Termination         Connector, N Male           Ingress Protection         -           Mounting Type         Panel Mount           Height (Max)         1.250" (31.75mm)           Applications         -	Frequency Range	890MHz ~ 960MHz
VSWR Return Loss - Gain 2.14dBi Power - Max - Features - Termination Connector, N Male Ingress Protection Mounting Type Panel Mount Height (Max) Applications -  Loss - Return Loss - Re	Antenna Type	Puck
Return Loss - Cain 2.14dBi  Power - Max - Features - Connector, N Male Ingress Protection - Connector Mounting Type Panel Mount Height (Max) 1.250" (31.75mm) Applications - Connector	Number of Bands	1
Gain2.14dBiPower - Max-Features-TerminationConnector, N MaleIngress Protection-Mounting TypePanel MountHeight (Max)1.250" (31.75mm)Applications-	VSWR	-
Power - Max Features Connector, N Male Ingress Protection - Mounting Type Panel Mount Height (Max) 1.250" (31.75mm) Applications	Return Loss	-
Features - Connector, N Male Ingress Protection - Panel Mount Height (Max) 1.250" (31.75mm) Applications	Gain	2.14dBi
Termination Connector, N Male Ingress Protection - Mounting Type Panel Mount Height (Max) 1.250" (31.75mm) Applications -	Power - Max	-
Ingress Protection - Mounting Type Panel Mount Height (Max) 1.250" (31.75mm) Applications -	Features	-
Mounting Type Panel Mount Height (Max) 1.250" (31.75mm) Applications -	Termination	Connector, N Male
Height (Max) Applications  1.250" (31.75mm) -	Ingress Protection	-
Applications -	Mounting Type	Panel Mount
	Height (Max)	1.250" (31.75mm)
Report errors?	Applications	-
		Report errors?

### 5606175 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 5606175 Payment Methods



















# **5606175 Shipping Methods**













If you have any question about 5606175, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com