



561R1DF0D22 Information

Heisener.com

Part Number 561R1DF0D22

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 2200PF 1KV N2800 RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









561R1DF0D22 Specifications

Manufacturer Part Number 561R1DF0D22 Manufacturer Vishay BC Components Category Capacitors Package Radial, Disc Series Cera-Mite 561R Capacitance 2200pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm) Lead Spacing Straight		
Category Capacitors Package Radial, Disc Series Cera-Mite 561R Capacitance 2200pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Manufacturer Part Number	561R1DF0D22
Package Radial, Disc Series Cera-Mite 561R Capacitance 2200pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Manufacturer	Vishay BC Components
Package Radial, Disc Series Cera-Mite 561R Capacitance 2200pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Category	Capacitors
Series Cera-Mite 561R Capacitance 2200pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)		Ceramic Capacitors
Capacitance 2200pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Package	Radial, Disc
Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Lead Spacing 0.252" (6.40mm)	Series	Cera-Mite 561R
Voltage - Rated 1000V (1kV) Temperature Coefficient N2800 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Case Nation 1.50 (Max) Lead Spacing 0.252" (6.40mm)	Capacitance	2200pF
Temperature Coefficient Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing N2800 - Some and Purpose General Purpose Factor Radial, Disc 0.461" Dia (11.70mm) - Lead Spacing 0.252" (6.40mm)	Tolerance	±10%
Operating Temperature Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing -55°C ~ 105°C Low Dissipation Factor Aby Dissipation Factor General Purpose Factor Factor Ageneral Purpose Factor Factor Ageneral Purpose Factor Factor Ageneral Purpose Factor Furough Hole Adial, Disc Radial, Disc Radial, Disc O.461" Dia (11.70mm) - Lead Spacing O.252" (6.40mm)	Voltage - Rated	1000V (1kV)
Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Temperature Coefficient	N2800
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Operating Temperature	-55°C ~ 105°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing O.252" (6.40mm)	Features	Low Dissipation Factor
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Applications	General Purpose
Package / Case Radial, Disc Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Failure Rate	-
Size / Dimension 0.461" Dia (11.70mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.252" (6.40mm)	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.252" (6.40mm)	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing - 0.252" (6.40mm)	Size / Dimension	0.461" Dia (11.70mm)
Lead Spacing 0.252" (6.40mm)	Height - Seated (Max)	-
	Thickness (Max)	-
Lead Style Straight	Lead Spacing	0.252" (6.40mm)
Ecad Style Straight	Lead Style	Straight
Report errors?		Report errors?

561R1DF0D22 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

561R1DF0D22 Payment Methods



















561R1DF0D22 Shipping Methods













If you have any question about 561R1DF0D22, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com