



561R1DF0Q39 Information

Heisener.com

Part Number 561R1DF0Q39

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 39PF 1KV N2200 RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









561R1DF0Q39 Specifications

| Manufacturer Part Number561R1DF0Q39ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadial, DiscSeriesCera-Mite 561RCapacitance39pFTolerance±10%Voltage - Rated1000V (1kV)Temperature CoefficientN2200Operating Temperature-55°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.252" Dia (6.40mm)Height - Seated (Max)-Thickness (Max)- | | |
|--|--------------------------|------------------------|
| Category Capacitors Package Radial, Disc Series Cera-Mite 561R Capacitance 39pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2200 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Manufacturer Part Number | 561R1DF0Q39 |
| PackageRadial, DiscSeriesCera-Mite 561RCapacitance39pFTolerance±10%Voltage - Rated1000V (1kV)Temperature CoefficientN2200Operating Temperature-55°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.252" Dia (6.40mm)Height - Seated (Max)- | Manufacturer | Vishay BC Components |
| PackageRadial, DiscSeriesCera-Mite 561RCapacitance39pFTolerance±10%Voltage - Rated1000V (1kV)Temperature CoefficientN2200Operating Temperature-55°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.252" Dia (6.40mm)Height - Seated (Max)- | Category | Capacitors |
| SeriesCera-Mite 561RCapacitance39pFTolerance±10%Voltage - Rated1000V (1kV)Temperature CoefficientN2200Operating Temperature-55°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.252" Dia (6.40mm)Height - Seated (Max)- | | Ceramic Capacitors |
| Capacitance39pFTolerance±10%Voltage - Rated1000V (1kV)Temperature CoefficientN2200Operating Temperature-55°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.252" Dia (6.40mm)Height - Seated (Max)- | Package | Radial, Disc |
| Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient N2200 Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) | Series | Cera-Mite 561R |
| Voltage - Rated1000V (1kV)Temperature CoefficientN2200Operating Temperature-55°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.252" Dia (6.40mm)Height - Seated (Max)- | Capacitance | 39pF |
| Temperature Coefficient Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) N2200 N2200 N2200 Low Dissipation Factor Low Dissipation Factor Factor In which is a company to the properties of the propertie | Tolerance | ±10% |
| Operating Temperature -55°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Voltage - Rated | 1000V (1kV) |
| Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Temperature Coefficient | N2200 |
| Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Operating Temperature | -55°C ~ 105°C |
| Applications General Purpose Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Features | Low Dissipation Factor |
| Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Ratings | - |
| Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Applications | General Purpose |
| Package / Case Radial, Disc Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Failure Rate | - |
| Size / Dimension 0.252" Dia (6.40mm) Height - Seated (Max) - | Mounting Type | Through Hole |
| Height - Seated (Max) | Package / Case | Radial, Disc |
| | Size / Dimension | 0.252" Dia (6.40mm) |
| Thickness (Max) | Height - Seated (Max) | - |
| | Thickness (Max) | - |
| Lead Spacing 0.252" (6.40mm) | Lead Spacing | 0.252" (6.40mm) |
| Lead Style Straight | Lead Style | Straight |
| Report errors? | | Report errors? |

561R1DF0Q39 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

561R1DF0Q39 Payment Methods



















561R1DF0Q39 Shipping Methods













If you have any question about 561R1DF0Q39, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com