



564PSB252K2R Information



For Reference Only

Part Number 564PSB252K2R

Manufacturer Illinois Capacitor

Category Capacitors

Film Capacitors

Description CAP FILM 0.56UF 10% 2.5KVDC RAD

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









564PSB252K2R Specifications

Manufacturer Part Number 564PSB252K2R Manufacturer Illinois Capacitors Category Capacitors Package Radial Series PSB Capacitance 0.56µF Tolerance ±10% Voltage Rating - AC 725V Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features - Report errors?	•		
Category Capacitors Film Capacitors Package Radial Series PSB Capacitance 0.56µF Tolerance ±10% Voltage Rating - AC 725V Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Manufacturer Part Number	564PSB252K2R	
$\begin{array}{c c} Film Capacitors \\ Package & Radial \\ Series & PSB \\ Capacitance & 0.56 \mu F \\ Tolerance & \pm 10 \% \\ Voltage Rating - AC & 725 V \\ Voltage Rating - DC & 2500V (2.5kV) \\ Dielectric Material & Polypropylene (PP), Metallized \\ ESR (Equivalent Series Resistance) & 4.3 mOhm \\ Operating Temperature & -40 ^{\circ}C \sim 100 ^{\circ}C \\ Mounting Type & Through Hole \\ Package / Case & Radial \\ Size / Dimension & 2.264 ^{\circ}L x 1.181 ^{\circ}W (57.50 mm x 30.00 mm) \\ Height - Seated (Max) & 1.772 ^{\circ} (45.00 mm) \\ Termination & PC Pins \\ Lead Spacing & 2.067 ^{\circ} (52.50 mm) \\ Applications & High Frequency, Switching; High Pulse, DV/DT; Snubber \\ Features & - \end{array}$	Manufacturer	Illinois Capacitor	
PackageRadialSeriesPSBCapacitance0.56μFTolerance±10%Voltage Rating - AC725VVoltage Ratirg - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)4.3 mOhmOperating Temperature-40°C ~ 100°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Category	Capacitors	
SeriesPSBCapacitance $0.56\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $725V$ Voltage Rating - DC $2500V (2.5kV)$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $2.264^{\circ}\text{L} \times 1.181^{\circ}\text{W} (57.50 \text{mm} \times 30.00 \text{mm})$ Height - Seated (Max) 1.772° (45.00 mm)TerminationPC PinsLead Spacing 2.067° (52.50 mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-		Film Capacitors	
Capacitance $0.56\mu F$ Tolerance $\pm 10\%$ Voltage Rating - AC $725V$ Voltage Rating - DC $2500V (2.5kV)$ Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$ Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $2.264^{\circ}\text{L x } 1.181^{\circ}\text{W } (57.50 \text{mm x } 30.00 \text{mm})$ Height - Seated (Max) 1.772° (45.00mm)TerminationPC PinsLead Spacing 2.067° (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package	Radial	
Tolerance ±10% Voltage Rating - AC 725V Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Series	PSB	
Voltage Rating - AC Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 4.3 mOhm -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Capacitance	0.56μF	
Voltage Rating - DC Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Tolerance	±10%	
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - AC	725V	
ESR (Equivalent Series Resistance) 4.3 mOhm Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Voltage Rating - DC	2500V (2.5kV)	
Operating Temperature -40°C ~ 100°C Mounting Type Through Hole Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Dielectric Material	Polypropylene (PP), Metallized	
Mounting Type Package / Case Radial Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	ESR (Equivalent Series Resistance)	4.3 mOhm	
Package / CaseRadialSize / Dimension2.264" L x 1.181" W (57.50mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Operating Temperature	-40°C ~ 100°C	
Size / Dimension 2.264" L x 1.181" W (57.50mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Mounting Type	Through Hole	
Height - Seated (Max) 1.772" (45.00mm) PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Package / Case	Radial	
Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Size / Dimension	2.264" L x 1.181" W (57.50mm x 30.00mm)	
Lead Spacing 2.067" (52.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Height - Seated (Max)	1.772" (45.00mm)	
Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Termination	PC Pins	
Features -	Lead Spacing	2.067" (52.50mm)	
	Applications	High Frequency, Switching; High Pulse, DV/DT; Snubber	
Report errors?	Features	-	
			Report errors?

564PSB252K2R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

564PSB252K2R Payment Methods





















564PSB252K2R Shipping Methods













If you have any question about 564PSB252K2R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com