

Heisener.com

564RC0HAJ602EJ6R8D

564RC0HAJ602EJ6R8D Information

Part Number 564RC0HAJ602EJ6R8D Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 6.8PF 6KV C0H RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









564RC0HAJ602EJ6R8D Specifications

Manufacturer Part Number \$64RC0HAJ602EJ6R8D Manufacturer Vishay BC Components Category Capacitors Package Radial, Disc Series Cera-Mite 564R Capacitance 6.8pF Tolerance ±0.5pF Voltage - Rated 6000V (6kV) Temperature Coefficient COH Operating Temperature -25°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight		
Category Capacitors Package Radial, Disc Series Cera-Mite 564R Capacitance 6.8pF Tolerance ±0.5pF Voltage - Rated 6000V (6kV) Temperature Coefficient COH Operating Temperature -25°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Manufacturer Part Number	564RC0HAJ602EJ6R8D
Package Radial, Disc Series Cera-Mite 564R Capacitance 6.8pF Tolerance ±0.5pF Voltage - Rated 6000V (6kV) Temperature Coefficient C0H Operating Temperature -25°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Manufacturer	Vishay BC Components
PackageRadial, DiscSeriesCera-Mite 564RCapacitance6.8pFTolerance±0.5pFVoltage - Rated6000V (6kV)Temperature CoefficientC0HOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Category	Capacitors
Series Cera-Mite 564R Capacitance 6.8pF Tolerance ±0.5pF Voltage - Rated 6000V (6kV) Temperature Coefficient C0H Operating Temperature -25°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight		Ceramic Capacitors
Capacitance6.8pFTolerance±0.5pFVoltage - Rated6000V (6kV)Temperature CoefficientC0HOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Package	Radial, Disc
Tolerance±0.5pFVoltage - Rated6000V (6kV)Temperature CoefficientC0HOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Series	Cera-Mite 564R
Voltage - Rated6000V (6kV)Temperature CoefficientC0HOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Capacitance	6.8pF
Temperature Coefficient Operating Temperature -25°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight	Tolerance	±0.5pF
Operating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Voltage - Rated	6000V (6kV)
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Lead Style	Temperature Coefficient	СОН
Ratings - General Purpose Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Ratings - General Purpose - Seneral Purpose - Straight - Stra	Operating Temperature	-25°C ~ 105°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Features	Low Dissipation Factor
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight Through Hole Radial, Disc Straight Straight	Applications	General Purpose
Package / Case Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Failure Rate	-
Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing Lead Style Straight	Size / Dimension	-
Lead Spacing-Lead StyleStraight	Height - Seated (Max)	-
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	Straight
		Report errors?

564RC0HAJ602EJ6R8D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

564RC0HAJ602EJ6R8D Payment Methods



















564RC0HAJ602EJ6R8D Shipping Methods













If you have any question about 564RC0HAJ602EJ6R8D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com