

Heisener.com

## 564RC0JAJ602EG3R9D

### 564RC0JAJ602EG3R9D Information

Part Number 564RC0JAJ602EG3R9D Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

**Description** CAP CER 3.9PF 6KV C0J RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 564RC0JAJ602EG3R9D Specifications

Manufacturer Part Number     564RC0JA1602EG3R9D       Manufacturer     Vishay BC Components       Category     Capacitors       Package     Radial, Disc       Series     Cera-Mite 564R       Capacitance     3.9pF       Tolerance     ±0.5pF       Voltage - Rated     6000V (6kV)       Temperature Coefficient     C0J       Operating Temperature     -25°C ~ 105°C       Features     Low Dissipation Factor       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Through Hole       Package / Case     Radial, Disc       Size / Dimension     -       Height - Seated (Max)     -       Thickness (Max)     -       Lead Spacing     -       Lead Spacing     -       Lead Style     Straight		
Category         Capacitors           Package         Radial, Disc           Series         Cera-Mite 564R           Capacitance         3.9pF           Tolerance         ±0.5pF           Voltage - Rated         6000V (6kV)           Temperature Coefficient         CUJ           Operating Temperature         -25°C ~ 105°C           Features         Low Dissipation Factor           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         -           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         Straight	Manufacturer Part Number	564RC0JAJ602EG3R9D
Package         Radial, Disc           Series         Cera-Mite 564R           Capacitance         3.9pF           Tolerance         ±0.5pF           Voltage - Rated         6000V (6kV)           Temperature Coefficient         C0J           Operating Temperature         -25°C ~ 105°C           Features         Low Dissipation Factor           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         -           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         Straight	Manufacturer	Vishay BC Components
PackageRadial, DiscSeriesCera-Mite 564RCapacitance3.9pFTolerance±0.5pFVoltage - Rated6000V (6kV)Temperature CoefficientCOJOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Category	Capacitors
Series         Cera-Mite 564R           Capacitance         3.9pF           Tolerance         ±0.5pF           Voltage - Rated         6000V (6kV)           Temperature Coefficient         COJ           Operating Temperature         -25°C ~ 105°C           Features         Low Dissipation Factor           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         -           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         Straight		Ceramic Capacitors
Capacitance3.9pFTolerance±0.5pFVoltage - Rated6000V (6kV)Temperature CoefficientCOJOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Package	Radial, Disc
Tolerance±0.5pFVoltage - Rated6000V (6kV)Temperature CoefficientC0JOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Series	Cera-Mite 564R
Voltage - Rated6000V (6kV)Temperature CoefficientCOJOperating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Capacitance	3.9pF
Temperature Coefficient Operating Temperature -25°C ~ 105°C Features Low Dissipation Factor Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight	Tolerance	±0.5pF
Operating Temperature-25°C ~ 105°CFeaturesLow Dissipation FactorRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead StyleStraight	Voltage - Rated	6000V (6kV)
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Lead Style	Temperature Coefficient	C0J
Ratings - General Purpose Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style  Ratings - General Purpose - Seneral Purpose - Straight - Stra	Operating Temperature	-25°C ~ 105°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Features	Low Dissipation Factor
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight Through Hole Radial, Disc Straight Straight	Applications	General Purpose
Package / Case Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Failure Rate	-
Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  Straight	Package / Case	Radial, Disc
Thickness (Max)  Lead Spacing  Lead Style  Straight	Size / Dimension	-
Lead Spacing-Lead StyleStraight	Height - Seated (Max)	-
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	Straight
		Report errors?

#### 564RC0JAJ602EG3R9D Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 564RC0JAJ602EG3R9D Payment Methods



















## 564RC0JAJ602EG3R9D Shipping Methods













If you have any question about 564RC0JAJ602EG3R9D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com