



### 570BAB001675DG Information



For Reference Only

Part Number 570BAB001675DG

Manufacturer Silicon Labs

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description** OSC XO 10-810MHZ LVDS SMD 3.3V

Package 8-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 570BAB001675DG Specifications

Manufacturer Part Number         570BAB001675DG           Manufacturer         Silicon Labs           Category         Crystals, Oscillators, Resonators           Programmable Oscillators         Programmable Oscillators           Package         8-SMD, No Lead           Series         Si570           Type         XO (Standard)           Programmable Type         Blank (User Must Program)           Available Frequency Range         10MHz ~ 810MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         3.3V           Frequency Stability         ±50ppm           Frequency Stability (Total)         ±61.5ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         108mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         8-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height         0.071" (1.80mm)		
Category         Crystals, Oscillators, Resonators           Package         8-SMD, No Lead           Series         Si570           Type         XO (Standard)           Programmable Type         Blank (User Must Program)           Available Frequency Range         10MHz ~ 810MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         3.3V           Frequency Stability (Total)         ±61.5ppm           Frequency Stability (Total)         ±61.5ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         108mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         8-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height         0.071" (1.80mm)	Manufacturer Part Number	570BAB001675DG
Package         8-SMD, No Lead           Series         Si570           Type         XO (Standard)           Programmable Type         Blank (User Must Program)           Available Frequency Range         10MHz ~ 810MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         3.3V           Frequency Stability         ±50ppm           Frequency Stability (Total)         ±61.5ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         108mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         8-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height         0.071" (1.80mm)	Manufacturer	Silicon Labs
Package         8-SMD, No Lead           Series         Si570           Type         XO (Standard)           Programmable Type         Blank (User Must Program)           Available Frequency Range         10MHz ~ 810MHz           Function         Enable/Disable           Output         LVDS           Voltage - Supply         3.3V           Frequency Stability         ±50ppm           Frequency Stability (Total)         ±61.5ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         108mA           Ratings         -           Mounting Type         Surface Mount           Package / Case         8-SMD, No Lead           Size / Dimension         0.276" L x 0.197" W (7.00mm x 5.00mm)           Height         0.071" (1.80mm)	Category	Crystals, Oscillators, Resonators
SeriesSi570TypeXO (Standard)Programmable TypeBlank (User Must Program)Available Frequency Range10MHz ~ 810MHzFunctionEnable/DisableOutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmFrequency Stability (Total)±61.5ppmOperating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)108mARatings-Mounting TypeSurface MountPackage / Case8-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.071" (1.80mm)		Programmable Oscillators
Type XO (Standard)  Programmable Type Blank (User Must Program)  Available Frequency Range 10MHz ~ 810MHz  Function Enable/Disable  Output LVDS  Voltage - Supply 3.3V  Frequency Stability ±50ppm  Frequency Stability (Total) ±61.5ppm  Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 108mA  Ratings -  Mounting Type Surface Mount  Package / Case 8-SMD, No Lead  Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height 0.071" (1.80mm)	Package	8-SMD, No Lead
Programmable Type  Available Frequency Range  10MHz ~ 810MHz  Function  Enable/Disable  Output  LVDS  Voltage - Supply  7 requency Stability  Frequency Stability (Total)  Operating Temperature  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Wounting Type  Surface Mount  Package / Case  Size / Dimension  Height  Blank (User Must Program)  Blank (User Must Program)  Blank (User Must Program)  10MHz ~ 810MHz  £ 10MHz  £ 10MHz  £ 10MHz  £ 10MHz  £ 50ppm  - 40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  108mA  8-SMD, No Lead  8-SMD, No Lead  10276" L x 0.197" W (7.00mm x 5.00mm)  10071" (1.80mm)	Series	Si570
Available Frequency Range  Function  Enable/Disable  Output  LVDS  Voltage - Supply  3.3V  Frequency Stability  ±50ppm  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  -  Current - Supply (Max)  Ratings  -  Mounting Type  Surface Mount  Package / Case  8-SMD, No Lead  Size / Dimension  0.071" (1.80mm)	Type	XO (Standard)
Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) ±61.5ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 108mA Ratings - Mounting Type Surface Mount Package / Case 8-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.0071" (1.80mm)	Programmable Type	Blank (User Must Program)
OutputLVDSVoltage - Supply3.3VFrequency Stability±50ppmFrequency Stability (Total)±61.5ppmOperating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)108mARatings-Mounting TypeSurface MountPackage / Case8-SMD, No LeadSize / Dimension0.276" L x 0.197" W (7.00mm x 5.00mm)Height0.071" (1.80mm)	Available Frequency Range	10MHz ~ 810MHz
Voltage - Supply  3.3V  Frequency Stability  Frequency Stability (Total)  Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  -  Current - Supply (Max)  Ratings  -  Mounting Type  Surface Mount  Package / Case  Size / Dimension  0.071" (1.80mm)  3.3V  3.3V  3.3V  450  Author Size / Domesion  3.3V  450  40°C ~ 85°C  -40°C ~ 8	Function	Enable/Disable
Frequency Stability (Total) ±61.5ppm  Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 108mA  Ratings -  Mounting Type Surface Mount  Package / Case 8-SMD, No Lead  Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height 0.071" (1.80mm)	Output	LVDS
Frequency Stability (Total) ±61.5ppm  Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 108mA  Ratings -  Mounting Type Surface Mount  Package / Case 8-SMD, No Lead  Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height 0.0071" (1.80mm)	Voltage - Supply	3.3V
Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 108mA  Ratings -  Mounting Type Surface Mount  Package / Case 8-SMD, No Lead  Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height 0.0071" (1.80mm)	Frequency Stability	±50ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 108mA Ratings - Mounting Type Surface Mount Package / Case 8-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Frequency Stability (Total)	±61.5ppm
Current - Supply (Max)  Ratings - Mounting Type Surface Mount Package / Case 8-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 8-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount  Package / Case 8-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)  Height 0.071" (1.80mm)	Current - Supply (Max)	108mA
Package / Case 8-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height 0.071" (1.80mm)	Ratings	-
Size / Dimension       0.276" L x 0.197" W (7.00mm x 5.00mm)         Height       0.071" (1.80mm)	Mounting Type	Surface Mount
Height 0.071" (1.80mm)	Package / Case	8-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height	0.071" (1.80mm)
		Report errors?

#### 570BAB001675DG Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 570BAB001675DG Payment Methods



















## 570BAB001675DG Shipping Methods













If you have any question about 570BAB001675DG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com