

58J9A45-01-2-03S Information

Heisener.com

Part Number 58J9A45-01-2-03S

Manufacturer Grayhill Inc.
Category Switches

Keylock Switches

Description SWITCH KEY 3POS DP3T 200MA 115V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









58J9A45-01-2-03S Specifications

Manufacturer Part Number 58J9A45-01-2-03S Manufacturer Grayhill Inc. Category Switches Package - Series 58 Circuit DP3T Number of Positions 3 Switch Function On-On-On Contact Timing Shorting (MBB) Current Rating 200mA (AC/DC) Voltage Rating - AC 115V Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic		
Category Switches Keylock Switches Package - Series S8 Circuit DP3T Number of Positions 3 Switch Function On-On-On Contact Timing Shorting (MBB) Current Rating 200mA (AC/DC) Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Features Antistatic	Manufacturer Part Number	58J9A45-01-2-03S
Reylock Switches Package - Series 58 Circuit DP3T Number of Positions 3 Switch Function On-On-On Contact Timing Shorting (MBB) Current Rating 200mA (AC/DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Features Key Sem Vericular - 19.05mm Dia Features	Manufacturer	Grayhill Inc.
Package - Series 58 Circuit DP3T Number of Positions 3 Switch Function On-On-On Contact Timing Shorting (MBB) Current Rating 200mA (AC/DC) Voltage Rating - AC 115V Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Category	Switches
Series 58 Circuit DP3T Number of Positions 3 Switch Function On-On-On Contact Timing Shorting (MBB) Current Rating 200mA (AC/DC) Voltage Rating - AC 115V Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic		Keylock Switches
CircuitDP3TNumber of Positions3Switch FunctionOn-On-OnContact TimingShorting (MBB)Current Rating200mA (AC/DC)Voltage Rating - AC115VVoltage Rating - DC30VActuator TypeFlat KeyKey Removable Positions1 and 180°Angle of Throw45°Contact Material-Contact FinishGold AlloyMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.05mm DiaFeaturesAntistatic	Package	-
Number of Positions3Switch FunctionOn-On-OnContact TimingShorting (MBB)Current Rating200mA (AC/DC)Voltage Rating - AC115VVoltage Rating - DC30VActuator TypeFlat KeyKey Removable Positions1 and 180°Angle of Throw45°Contact Material-Contact FinishGold AlloyMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.05mm DiaFeaturesAntistatic	Series	58
Switch FunctionOn-On-OnContact TimingShorting (MBB)Current Rating200mA (AC/DC)Voltage Rating - AC115VVoltage Rating - DC30VActuator TypeFlat KeyKey Removable Positions1 and 180°Angle of Throw45°Contact Material-Contact FinishGold AlloyMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.05mm DiaFeaturesAntistatic	Circuit	DP3T
Contact Timing Shorting (MBB) Current Rating 200mA (AC/DC) Voltage Rating - AC 115V Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Annual AC/DC) Shorting (MBB) Command (MBB) Shorting (MBB) Solder Lug Antistatic	Number of Positions	3
Current Rating 200mA (AC/DC) Voltage Rating - AC 115V Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Switch Function	On-On-On
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Flat Key Key Removable Positions Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Features 115V 30V 30V 30V 30V 60ld Rey 60ld Alloy 6	Contact Timing	Shorting (MBB)
Voltage Rating - DC Actuator Type Flat Key Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 19.05mm Dia Antistatic	Current Rating	200mA (AC/DC)
Actuator Type Key Removable Positions 1 and 180° Angle of Throw 45° Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 19.05mm Dia Features Flat Key Flat Hellow Aftistatic	Voltage Rating - AC	115V
Key Removable Positions1 and 180°Angle of Throw45°Contact Material-Contact FinishGold AlloyMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.05mm DiaFeaturesAntistatic	Voltage Rating - DC	30V
Angle of Throw Contact Material Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Actuator Type	Flat Key
Contact Material - Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Key Removable Positions	1 and 180°
Contact Finish Gold Alloy Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Angle of Throw	45°
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Contact Material	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Contact Finish	Gold Alloy
Panel Cutout Dimensions Circular - 19.05mm Dia Features Antistatic	Mounting Type	Panel Mount
Features Antistatic	Termination Style	Solder Lug
	Panel Cutout Dimensions	Circular - 19.05mm Dia
Report errors?	Features	Antistatic
		Report errors?

58J9A45-01-2-03S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

58J9A45-01-2-03S Payment Methods



















58J9A45-01-2-03S Shipping Methods













If you have any question about 58J9A45-01-2-03S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com