

# 595D107X0016D2T

## 595D107X0016D2T Information

writereisenariom	 595D107X0016D2T Vishay Sprague Capacitors Tantalum Capacitors CAP TANT 100UF 16V 20% 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 595D107X0016D2T Specifications

ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, 595DCapacitance100µFTolerance±20%Voltage - Rated16VTypeConformal CoatedSeries Resistance)140 mOhmOperating Temperature-S5°C ~ 125°CLifetime @ Temp.Surface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295° L x 0.169° W (7.50mm x 4.30mm)Height - Seated (Max)0.122° (3.10mm)Lied SpacingDFaturesMounting Tuppe			
CategoryCapacitorsCategoryCapacitorsPackage2917 (7343 Metric)Package2917 (7343 Metric)SeriesTANTAMOUNT?, 595DCapacitance100µFTolerance±20%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295° L x 0.169° W (7.50mm x 4.30mm)Height - Seated (Max)0.122″ (3.10mm)Lead Spacing-FacturesGeneral Purpose	Manufacturer Part Number	595D107X0016D2T	
Tantalum CapacitorsPackage2917 (7343 Metric)SeriesTANTAMOUNT?, 595DCapacitance100µFTolerance±20%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-FeaturesGeneral Purpose	Manufacturer	Vishay Sprague	
Package2917 (7343 Metric)SeriesTANTAMOUNT?, 595DCapacitance100µFTolerance±20%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead SpacingDFeaturesGeneral Purpose	Category	Capacitors	
SeriesTANTAMOUNT?, 595DCapacitance100µFTolerance±20%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead SpacingDFeaturesGeneral Purpose		Tantalum Capacitors	
Capacitance100μFTolerance±20%Voltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ Temp.Surface MountMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead SpacingDFeaturesGeneral Purpose	Package	2917 (7343 Metric)	
Tolerance±20%Yoltage - Rated16VTypeConformal CoatedType140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295° L x 0.169° W (7.50mm x 4.30mm)Height - Seated (Max)0.122° (3.10mm)Lead Spacing-FeaturesGeneral Purpose	Series	TANTAMOUNT?, 595D	
NotifiedInterferenceVoltage - Rated16VTypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Capacitance	100µF	
TypeConformal CoatedESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead SpacingDManufacturer Size CodeDFeaturesGeneral Purpose	Tolerance	±20%	
Fraction140 mOhmESR (Equivalent Series Resistance)140 mOhmOperating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Voltage - Rated	16V	
No. 1-55°C ~ 125°CLifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Туре	Conformal Coated	
Lifetime @ TempMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	140 mOhm	
Mounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 125°C	
Package / Case2917 (7343 Metric)Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Lifetime @ Temp.	-	
Size / Dimension0.295" L x 0.169" W (7.50mm x 4.30mm)Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Mounting Type	Surface Mount	
Height - Seated (Max)0.122" (3.10mm)Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)	
Lead Spacing-Manufacturer Size CodeDFeaturesGeneral Purpose	Size / Dimension	0.295" L x 0.169" W (7.50mm x 4.30mm)	
Manufacturer Size CodeDFeaturesGeneral Purpose	Height - Seated (Max)	0.122" (3.10mm)	
Features General Purpose	Lead Spacing	_	
1	Manufacturer Size Code	D	
Failure Rate -	Features	General Purpose	
	Failure Rate	-	
Report errors?			Report errors?

#### 595D107X0016D2T Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### 595D107X0016D2T Payment Methods





If you have any question about 595D107X0016D2T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com