

5973402107F

Request a Quote

5973402107F Information

Heisener.com	Part Number	5973402107F
	Manufacturer	Dialight
	Category	Optoelectronics LED Indication - Discrete
	Description	LED YELLOW 1210 SMD
	Package	1210 (3125 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5973402107F Specifications

Manufacturer Part Number 5973402107F Manufacturer Dialight Category Optoelectronics LED Indication - Discrete EED Indication - Discrete Package 1210 (3125 Metric) Series 597 Color Yellow Configuration Yellow Lens Tansparency - Multiandela Rating 6mcd Voltage - Forward (Vf) (Typ) - Viewing Angle - Viewing Angle Samma Vavelength - Dominant Samma Vavelength - Peakage - Starkage / Case 1210 (3125 Metric) Supplier Device Package 1210 (3125 Metric) Supplier Device Package - Starkage / Case - Size / Dimension - Size / Dimension - Size / Dimension - Houting Houting Houting -		
CategoryOptoelectronicsLED Indication - DiscretePackage1210 (3125 Metric)Series597ColorYellowConfiguration-Lens Color-Lens Transparency-Millicandela Rating6mcdVoltage - Forward (Vf) (Typ)-Current - Test10mANounting TypeSammaWavelength - PonkanSammaYavelength - Peak-Features201 (3125 Metric)Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension210Height (Max)-Height (Max)-Height (Max)-State Construction-State	Manufacturer Part Number	5973402107F
Leb Indication - DiscretePackage1210 (3125 Metric)Series597ColorYellowConfiguration-Lens Color-Lens Transparency-Millicandela Rating6mcdLens Style/Size-Voltage - Forward (Vf) (Typ)-Current - Test10mAWounting TypeSurface MountWavelength - Dominant588nmWavelength - Peak-Features1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-Height (Max)-	Manufacturer	Dialight
Package1210 (3125 Metric)Series597ColorYellowColorYellowConfiguration-Lens Color-Lens Transparency-Millicandela RatingGmcdLens Style/Size-Voltage - Forward (Vf) (Typ)-Voltage - Forward (Vf) (Typ)-Viewing Angle-Youring TypeSamanMunting TypeSamanWavelength - Dominant-Wavelength - Peak-Package / Case1210 (3125 Metric)Supplier Device Package210Size / Dimension-Height (Max)-Height (Max)-Soman-Size / Dimension-Height (Max)-Soman-Size / Dimension-Size	Category	Optoelectronics
<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>		LED Indication - Discrete
ColorYellowConfiguration-Lens Color-Lens Color-Lens Transparency-Milicandela Rating6mcdLens Style/Size-Voltage - Forward (Vf (Typ)-Current - Test10mAVoltaging Angle-Mouting TypeSurface MountWavelength - PomiantStafke MountVavelength - Peak-Package / Case1210 (3125 Metric)Suppler Device Package-Size / Dimension-Height (Max)-Size / Dimension-Height (Max)-Stafe (Max)-Stafe (Max)-Size / Dimension-Stafe (Max)-Stafe (Max)-	Package	1210 (3125 Metric)
Configuration-Lens Color-Lens Transparency-Milicandel Rating6mcdLens Style/Size-Voltage - Forward (Vf) (Typ)-Current - Test10mAVoltaging Angle-Vavelength - DominantStafkae MountWavelength - Peak-Features-Package / Case-Supplier Device Package1210Stafe / Dimension-Stafe / Dimension-Stafe / Dimension-Height (Max)-Stafe / Dimension-Stafe / Dimension- <t< td=""><td>Series</td><td>597</td></t<>	Series	597
Lens-Lens Transparency-Milicandela Rating6mcdLens Style/Size-Voltage - Forward (Vf) (Typ)-Current - Test10mAViewing Angle-Mounting TypeSurface MountWavelength - Poak588nmWavelength - Peak-Features1010 (3125 Metric)Suppler Device Package1210Size / Dimension-Height (Max)-Height (Max)-	Color	Yellow
Lens Transparency-Milicande Rating6mcdLens Style/Size-Voltage - Forward (Vf) (Typ)-Current - Test10mANouting Type-Mouting TypeStafface MountWavelength - Poak588nnWavelength - Peak-Features1210 (3125 Metric)Stappier Device Package1210Size / Dimension-Height (Max)-Height (Max)-Height (Max)-Stappier Device Package-Stappier D	Configuration	-
Millicandela Rating6mcdLens Style/Size-Voltage - Forward (Vf) (Typ)-Current - Test10mAViewing Angle-Mounting TypeSurface MountWavelength - Dominant588mWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-Height (Max)-State Construction-State Construction-	Lens Color	-
Lens Style/Size-Voltage - Forward (Vf) (Typ)-Current - Test10mAViewing Angle-Mounting TypeSurface MountWavelength - Dominant588nmWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package-Size / Dimension-Height (Max)-Stel (Max)-	Lens Transparency	-
Voltage - Forward (Vf) (Typ)-Current - Test10mAViewing Angle-Mounting TypeSurface MountWavelength - Dominant588nmWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package-Size / Dimension-Height (Max)-	Millicandela Rating	6mcd
Current - Test10mAViewing Angle-Mounting TypeSurface MountWavelength - Dominant588nmWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package-Size / Dimension-Height (Max)-	Lens Style/Size	-
Viewing Angle-Mounting TypeSurface MountWavelength - Dominant588nmWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-	Voltage - Forward (Vf) (Typ)	-
Mounting TypeSurface MountWavelength - Dominant588nmWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-	Current - Test	10mA
Wavelength - Dominant588nmWavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-	Viewing Angle	-
Wavelength - Peak-Features-Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-	Mounting Type	Surface Mount
Features-Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-	Wavelength - Dominant	588nm
Package / Case1210 (3125 Metric)Supplier Device Package1210Size / Dimension-Height (Max)-	Wavelength - Peak	-
Supplier Device Package1210Size / Dimension-Height (Max)-	Features	-
Size / Dimension - Height (Max) -	Package / Case	1210 (3125 Metric)
Height (Max) -	Supplier Device Package	1210
-	Size / Dimension	-
Report errors?	Height (Max)	-
		Report errors?

5973402107F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

5973402107F Payment Methods WIRE PayPal WIRE INVINE MARKED IN ALLER IN ALL

If you have any question about 5973402107F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com