

### 5977731107F Information



For Reference Only

Part Number 5977731107F Manufacturer Dialight

**Category** Optoelectronics

LED Indication - Discrete

**Description** LED RED/YLW CLEAR 4SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **5977731107F Specifications**

Manufacturer Part Number         5977731107F           Manufacturer         Dialight           Category         Optoelectronics           LED Indication - Discrete           Package         4-SMD, No Lead           Series         microLED?           Color         Red, Yellow           Configuration         Independent           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         4mcd Red, 8mcd Yellow           Lens Style/Size         Rectangle with Flat Top, 1.65mm x 1.27mm           Voltage - Forward (Vf) (Typ)         2V Red, 2.1V Yellow           Current - Test         20mA Red, 20mA Yellow           Viewing Angle         170°           Mounting Type         Surface Mount           Wavelength - Dominant         620nm Red, 585nm Yellow           Wavelength - Peak         630nm Red, 585nm Yellow           Wavelength - Peak         630nm Red, 585nm Yellow           Peatures         -           Peakage / Case         4-SMD, No Lead           Supplier Device Package         4-SMD, No Lead           Supplier Device Package         4-SMD           Size / Dimension         3.00mm L x 2.54mm W           Height (Max)	•		
Category         Optoelectronics           LED Indication - Discrete           Package         4-SMD, No Lead           Series         microLED?           Color         Red, Yellow           Configuration         Independent           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         4mcd Red, 8mcd Yellow           Lens Style/Size         Rectangle with Flat Top, 1.65mm x 1.27mm           Voltage - Forward (Vf) (Typ)         2V Red, 2.1V Yellow           Current - Test         20mA Red, 20mA Yellow           Viewing Angle         170°           Mounting Type         Surface Mount           Wavelength - Dominant         620nm Red, 585nm Yellow           Wavelength - Peak         630nm Red, 585nm Yellow           Features         -           Package / Case         4-SMD, No Lead           Supplier Device Package         4-SMD           Size / Dimension         3.00mm L x 2.54mm W           Height (Max)         1.02mm	Manufacturer Part Number	5977731107F	
Package         4-SMD, No Lead           Series         microLED?           Color         Red, Yellow           Configuration         Independent           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         4mcd Red, 8mcd Yellow           Lens Style/Size         Rectangle with Flat Top, 1.65mm x 1.27mm           Voltage - Forward (Vf) (Typ)         2V Red, 2.1V Yellow           Current - Test         20mA Red, 20mA Yellow           Viewing Angle         170°           Mounting Type         Surface Mount           Wavelength - Dominant         620nm Red, 585nm Yellow           Wavelength - Peak         630nm Red, 585nm Yellow           Features         -           Package / Case         4-SMD, No Lead           Supplier Device Package         4-SMD           Size / Dimension         3.00mm L x 2.54mm W           Height (Max)         1.02mm	Manufacturer	Dialight	
Package         4-SMD, No Lead           Series         microLED?           Color         Red, Yellow           Configuration         Independent           Lens Color         Colorless           Lens Transparency         Clear           Millicandela Rating         4mcd Red, 8mcd Yellow           Lens Style/Size         Rectangle with Flat Top, 1.65mm x 1.27mm           Voltage - Forward (Vf) (Typ)         2V Red, 2.1V Yellow           Current - Test         20mA Red, 20mA Yellow           Viewing Angle         170°           Mounting Type         Surface Mount           Wavelength - Dominant         620nm Red, 585nm Yellow           Wavelength - Peak         630nm Red, 585nm Yellow           Features         -           Package / Case         4-SMD, No Lead           Supplier Device Package         4-SMD           Size / Dimension         3.00mm L x 2.54mm W           Height (Max)         1.02mm	Category	Optoelectronics	
SeriesmicroLED?ColorRed, YellowConfigurationIndependentLens ColorColorlessLens TransparencyClearMillicandela Rating4mcd Red, 8mcd YellowLens Style/SizeRectangle with Flat Top, 1.65mm x 1.27mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle170°Mounting TypeSurface MountWavelength - Dominant620nm Red, 585nm YellowWavelength - Peak630nm Red, 585nm YellowFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.00mm L x 2.54mm WHeight (Max)1.02mm		LED Indication - Discrete	
ColorRed, YellowConfigurationIndependentLens ColorColorlessLens TransparencyClearMillicandela Rating4mcd Red, 8mcd YellowLens Style/SizeRectangle with Flat Top, 1.65mm x 1.27mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle170°Mounting TypeSurface MountWavelength - Dominant620nm Red, 585nm YellowWavelength - Peak630nm Red, 585nm YellowFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.00mm L x 2.54mm WHeight (Max)1.02mm	Package	4-SMD, No Lead	
ConfigurationIndependentLens ColorColorlessLens TransparencyClearMillicandela Rating4mcd Red, 8mcd YellowLens Style/SizeRectangle with Flat Top, 1.65mm x 1.27mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle170°Mounting TypeSurface MountWavelength - Dominant620nm Red, 585nm YellowWavelength - Peak630nm Red, 585nm YellowFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.00mm L x 2.54mm WHeight (Max)1.02mm	Series	microLED?	
Lens ColorColorlessLens TransparencyClearMillicandela Rating4mcd Red, 8mcd YellowLens Style/SizeRectangle with Flat Top, 1.65mm x 1.27mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle170°Mounting TypeSurface MountWavelength - Dominant620nm Red, 585nm YellowWavelength - Peak630nm Red, 585nm YellowFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.00mm L x 2.54mm WHeight (Max)1.02mm	Color	Red, Yellow	
Lens TransparencyClearMillicandela Rating4mcd Red, 8mcd YellowLens Style/SizeRectangle with Flat Top, 1.65mm x 1.27mmVoltage - Forward (Vf) (Typ)2V Red, 2.1V YellowCurrent - Test20mA Red, 20mA YellowViewing Angle170°Mounting TypeSurface MountWavelength - Dominant620nm Red, 585nm YellowWavelength - Peak630nm Red, 585nm YellowFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.00mm L x 2.54mm WHeight (Max)1.02mm	Configuration	Independent	
Millicandela Rating  Lens Style/Size  Rectangle with Flat Top, 1.65mm x 1.27mm  Voltage - Forward (Vf) (Typ)  2V Red, 2.1V Yellow  Current - Test  20mA Red, 20mA Yellow  Viewing Angle  170°  Mounting Type  Surface Mount  620nm Red, 585nm Yellow  Wavelength - Dominant  620nm Red, 585nm Yellow  Wavelength - Peak  630nm Red, 585nm Yellow  Features  - Package / Case  4-SMD, No Lead  Supplier Device Package  4-SMD  Size / Dimension  3.00mm L x 2.54mm W  Height (Max)  1.02mm	Lens Color	Colorless	
Lens Style/Size Rectangle with Flat Top, 1.65mm x 1.27mm  Voltage - Forward (Vf) (Typ) 2V Red, 2.1V Yellow  Current - Test 20mA Red, 20mA Yellow  Viewing Angle 170°  Mounting Type Surface Mount  Wavelength - Dominant 620nm Red, 585nm Yellow  Wavelength - Peak 630nm Red, 585nm Yellow  Features - Package / Case 4-SMD, No Lead  Supplier Device Package 4-SMD  Size / Dimension 3.00mm L x 2.54mm W  Height (Max) 1.02mm	Lens Transparency	Clear	
Voltage - Forward (Vf) (Typ)  2V Red, 2.1V Yellow  Current - Test  20mA Red, 20mA Yellow  Viewing Angle  170°  Mounting Type  Surface Mount  620nm Red, 585nm Yellow  Wavelength - Dominant  620nm Red, 585nm Yellow  630nm Red, 585nm Yellow  Features  - Package / Case  4-SMD, No Lead  Supplier Device Package  4-SMD  Size / Dimension  3.00mm L x 2.54mm W  Height (Max)  1.02mm	Millicandela Rating	4mcd Red, 8mcd Yellow	
Current - Test 20mA Red, 20mA Yellow Viewing Angle 170° Mounting Type Surface Mount Wavelength - Dominant 620nm Red, 585nm Yellow Wavelength - Peak 630nm Red, 585nm Yellow Features - Package / Case 4-SMD, No Lead Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Lens Style/Size	Rectangle with Flat Top, 1.65mm x 1.27mm	
Viewing Angle170°Mounting TypeSurface MountWavelength - Dominant620nm Red, 585nm YellowWavelength - Peak630nm Red, 585nm YellowFeatures-Package / Case4-SMD, No LeadSupplier Device Package4-SMDSize / Dimension3.00mm L x 2.54mm WHeight (Max)1.02mm	Voltage - Forward (Vf) (Typ)	2V Red, 2.1V Yellow	
Mounting Type Surface Mount  Wavelength - Dominant 620nm Red, 585nm Yellow Wavelength - Peak 630nm Red, 585nm Yellow Features - Package / Case 4-SMD, No Lead Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Current - Test	20mA Red, 20mA Yellow	
Wavelength - Dominant 620nm Red, 585nm Yellow Wavelength - Peak 630nm Red, 585nm Yellow Features - Package / Case 4-SMD, No Lead Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Viewing Angle	170°	
Wavelength - Peak 630nm Red, 585nm Yellow Features - Package / Case 4-SMD, No Lead Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Mounting Type	Surface Mount	
Features - Package / Case 4-SMD, No Lead Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Wavelength - Dominant	620nm Red, 585nm Yellow	
Package / Case 4-SMD, No Lead Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Wavelength - Peak	630nm Red, 585nm Yellow	
Supplier Device Package 4-SMD Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Features	-	
Size / Dimension 3.00mm L x 2.54mm W Height (Max) 1.02mm	Package / Case	4-SMD, No Lead	
Height (Max) 1.02mm	Supplier Device Package	4-SMD	
	Size / Dimension	3.00mm L x 2.54mm W	
Report errors?	Height (Max)	1.02mm	
			Report errors?

#### 5977731107F Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 5977731107F Payment Methods



















## 5977731107F Shipping Methods













If you have any question about 5977731107F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com