

5988230107F

5988230107F Information

	Part Number	5988230107F
	Manufacturer	Dialight
www.heisener.com	Category	Optoelectronics LED Indication - Discrete
	Description	LED ORANGE CLEAR 1206 SMD
	Package	1206 (3216 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5988230107F Specifications

ManufacturerDialightCategoryOptoelectronicsLED Indication - DiscretePackage1206 (3216 Metric)Series598ColorOrangeConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating110mcdVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	•		
Decemp Decemp Category Decelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series 598 Color Orange Colfiguration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 110mcd Lens Style/Size Rectangle with Flat Top, 2.00mm x 1.60mm Voltage - Forward (Vf) (Typ) 2V Current - Test 20mA Wavelength - Dominant 605nm Wavelength - Peak - Features - Package / Case 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Size / Dimension 3.20mm L x 1.60mm W Height (Max) 0.70mm	Manufacturer Part Number	5988230107F	
LED Indication - DiscretePackage1206 (3216 Metric)Series598ColorOrangeConfiguration-Lens ColorColorlessLens TansparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmVavelength - Peak-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Manufacturer	Dialight	
Package1206 (3216 Metric)Series598ColorOrangeConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAWouting Type605nmWavelength - Pominant-Vavelength - Peak-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WBight (Max)0.70mm	Category	Optoelectronics	
Series598ColorOrangeConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mANounting TypeSurface MountWavelength - Dominant605mmWavelength - Peak-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm		LED Indication - Discrete	
ColorOrangeConfiguration-Lens ColorColorlessLens TransparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAVoltage AngleSurface MountWavelength - Dominant605nmWavelength - Peak-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm Lx 1.60mm WHeight (Max)0.70mm	Package	1206 (3216 Metric)	
Configuration-Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)0.70mm	Series	598	
Lens ColorColorlessLens TransparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mACurrent - Test20mAWounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features.Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)0.70mm	Color	Orange	
Lens TransparencyClearMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Configuration	-	
Millicandela Rating110mcdMillicandela Rating110mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Lens Color	Colorless	
Lens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Lens Transparency	Clear	
Voltage - Forward (Vf) (Typ)2VCurrent - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Millicandela Rating	110mcd	
Current - Test20mAViewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Lens Style/Size	Rectangle with Flat Top, 2.00mm x 1.60mm	
Viewing Angle140°Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Voltage - Forward (Vf) (Typ)	2V	
Mounting TypeSurface MountWavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Current - Test	20mA	
Wavelength - Dominant605nmWavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Viewing Angle	140°	
Wavelength - Peak-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Mounting Type	Surface Mount	
Features-Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Wavelength - Dominant	605nm	
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Wavelength - Peak	-	
Supplier Device Package1206Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Features	-	
Size / Dimension3.20mm L x 1.60mm WHeight (Max)0.70mm	Package / Case	1206 (3216 Metric)	
Height (Max) 0.70mm	Supplier Device Package	1206	
•	Size / Dimension	3.20mm L x 1.60mm W	
Report errors?	Height (Max)	0.70mm	
		Report errors?	

5988230107F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

5988230107F Payment Methods Image: Several s

If you have any question about 5988230107F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com