

5988721307F Information

.heisenei

5988721307F Part Number Manufacturer Dialight

Category Optoelectronics

LED Indication - Discrete

Description LED RGB CLEAR 0606 SMD

0606 (1616 Metric) **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5988721307F Specifications

Manufacturer Part Number 5988721307F Manufacturer Dialight Category Optoelectronics LED Indication - Discrete Package 0606 (1616 Metric) Series 598 Color Red, Green, Blue (RGB) Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 80mcd Red-Orange, 150mcd Green, 60mcd Blue Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm Report errors?	•	
Category Optoelectronics LED Indication - Discrete Package 0606 (1616 Metric) Series 598 Color Red, Green, Blue (RGB) Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 80mcd Red-Orange, 150mcd Green, 60mcd Blue Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Manufacturer Part Number	5988721307F
Package 0606 (1616 Metric) Series 598 Color Red, Green, Blue (RGB) Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 80mcd Red-Orange, 150mcd Green, 60mcd Blue Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Manufacturer	Dialight
Package 0606 (1616 Metric) Series 598 Color Red, Green, Blue (RGB) Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 80mcd Red-Orange, 150mcd Green, 60mcd Blue Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Category	Optoelectronics
Series598ColorRed, Green, Blue (RGB)Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating80mcd Red-Orange, 150mcd Green, 60mcd BlueLens Style/SizeRectangle with Flat Top, 1.10mm x 0.90mmVoltage - Forward (Vf) (Typ)2.2V Red-Orange, 3V Green, 3.2V BlueCurrent - Test20mA Red-Orange, 20mA Green, 20mA BlueViewing Angle140°Mounting TypeSurface MountWavelength - Dominant625nm Red-Orange, 525nm Green, 470nm BlueWavelength - Peak-Features-Package / Case0606 (1616 Metric)Supplier Device Package-Size / Dimension1.60mm L x 1.60mm WHeight (Max)0.70mm		LED Indication - Discrete
ColorRed, Green, Blue (RGB)Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating80mcd Red-Orange, 150mcd Green, 60mcd BlueLens Style/SizeRectangle with Flat Top, 1.10mm x 0.90mmVoltage - Forward (Vf) (Typ)2.2V Red-Orange, 3V Green, 3.2V BlueCurrent - Test20mA Red-Orange, 20mA Green, 20mA BlueViewing Angle140°Mounting TypeSurface MountWavelength - Dominant625nm Red-Orange, 525nm Green, 470nm BlueWavelength - Peak-Features-Package / Case0606 (1616 Metric)Supplier Device Package-Size / Dimension1.60mm L x 1.60mm WHeight (Max)0.70mm	Package	0606 (1616 Metric)
Configuration - Colorless Lens Transparency Clear Millicandela Rating 80mcd Red-Orange, 150mcd Green, 60mcd Blue Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Series	598
Lens ColorColorlessLens TransparencyClearMillicandela Rating80mcd Red-Orange, 150mcd Green, 60mcd BlueLens Style/SizeRectangle with Flat Top, 1.10mm x 0.90mmVoltage - Forward (Vf) (Typ)2.2V Red-Orange, 3V Green, 3.2V BlueCurrent - Test20mA Red-Orange, 20mA Green, 20mA BlueViewing Angle140°Mounting TypeSurface MountWavelength - Dominant625nm Red-Orange, 525nm Green, 470nm BlueWavelength - Peak-Features-Package / Case0606 (1616 Metric)Supplier Device Package-Size / Dimension1.60mm L x 1.60mm WHeight (Max)0.70mm	Color	Red, Green, Blue (RGB)
Lens TransparencyClearMillicandela Rating80mcd Red-Orange, 150mcd Green, 60mcd BlueLens Style/SizeRectangle with Flat Top, 1.10mm x 0.90mmVoltage - Forward (Vf) (Typ)2.2V Red-Orange, 3V Green, 3.2V BlueCurrent - Test20mA Red-Orange, 20mA Green, 20mA BlueViewing Angle140°Mounting TypeSurface MountWavelength - Dominant625nm Red-Orange, 525nm Green, 470nm BlueWavelength - Peak-Features-Package / Case0606 (1616 Metric)Supplier Device Package-Size / Dimension1.60mm L x 1.60mm WHeight (Max)0.70mm	Configuration	-
Millicandela Rating Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle Mounting Type Surface Mount 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Lens Color	Colorless
Lens Style/Size Rectangle with Flat Top, 1.10mm x 0.90mm Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) 2.2V Red-Orange, 3V Green, 3.2V Blue Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Viewing Angle Viewing Angle Surface Mount 625nm Red-Orange, 525nm Green, 470nm Blue - Comparison - Comparison 1.60mm L x 1.60mm W Height (Max) 0.70mm	Millicandela Rating	80mcd Red-Orange, 150mcd Green, 60mcd Blue
Current - Test 20mA Red-Orange, 20mA Green, 20mA Blue Viewing Angle 140° Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Lens Style/Size	Rectangle with Flat Top, 1.10mm x 0.90mm
Viewing Angle140°Mounting TypeSurface MountWavelength - Dominant625nm Red-Orange, 525nm Green, 470nm BlueWavelength - Peak-Features-Package / Case0606 (1616 Metric)Supplier Device Package-Size / Dimension1.60mm L x 1.60mm WHeight (Max)0.70mm	Voltage - Forward (Vf) (Typ)	2.2V Red-Orange, 3V Green, 3.2V Blue
Mounting Type Surface Mount Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Current - Test	20mA Red-Orange, 20mA Green, 20mA Blue
Wavelength - Dominant 625nm Red-Orange, 525nm Green, 470nm Blue Wavelength - Peak - Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Viewing Angle	140°
Wavelength - Peak Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Mounting Type	Surface Mount
Features - Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Wavelength - Dominant	625nm Red-Orange, 525nm Green, 470nm Blue
Package / Case 0606 (1616 Metric) Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Wavelength - Peak	-
Supplier Device Package - Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Features	-
Size / Dimension 1.60mm L x 1.60mm W Height (Max) 0.70mm	Package / Case	0606 (1616 Metric)
Height (Max) 0.70mm	Supplier Device Package	-
	Size / Dimension	1.60mm L x 1.60mm W
Report errors?	Height (Max)	0.70mm
		Report errors?

5988721307F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5988721307F Payment Methods



















5988721307F Shipping Methods













If you have any question about 5988721307F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com