



5AK220KOBQL Information



For Reference Only

Part Number 5AK220KOBQL Manufacturer AVX Corporation Category Capacitors

Ceramic Capacitors

Description CAP CER 22PF 100V NP0 RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5AK220KOBQL Specifications

Manufacturer Part Number 5AK220KOBQL Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 22pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked		
Category Capacitors Package Radial, Disc Series - Capacitance 22pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Manufacturer Part Number	5AK220KOBQL
Package Radial, Disc Series - Capacitance 22pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 22pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Category	Capacitors
Series - Capacitance 22pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)		Ceramic Capacitors
Capacitance 22pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Package	Radial, Disc
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -30°C ~ 85°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) Lead Spacing 0.197" (5.00mm)	Series	-
Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 100V COG, NP0 COG, NP0 COG, NP0 Through Hole - Ratings - Unional Hole - Congress (Max) 100V Congress (NP0 Cong	Capacitance	22pF
Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing COG, NPO -30°C ~ 85°C - Round - Though Hole - Connect Purpose - Through Hole Radial, Disc Radial, Disc 0.197" Dia (5.00mm) - Lead Spacing 0.197" (5.00mm)	Tolerance	±10%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing -30°C ~ 85°C -30	Voltage - Rated	100V
Features - General Purpose - General Purpose - General Purpose - Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) - Lead Spacing 0.197" (5.00mm)	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Features	-
Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)	Failure Rate	-
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	Package / Case	Radial, Disc
Thickness (Max) - Lead Spacing - 0.197" (5.00mm)	Size / Dimension	0.197" Dia (5.00mm)
Lead Spacing 0.197" (5.00mm)	Height - Seated (Max)	0.157" (4.00mm)
	Thickness (Max)	-
Lead Style Formed Leads - Kinked	Lead Spacing	0.197" (5.00mm)
	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

5AK220KOBQL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5AK220KOBQL Payment Methods



















5AK220KOBQL Shipping Methods













If you have any question about 5AK220KOBQL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com