



5AK330JABAK Information



For Reference Only

Part Number 5AK330JABAK
Manufacturer AVX Corporation
Category Capacitors

Capacitors
Ceramic Capacitors

Description CAP CER 33PF 100V NP0 RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5AK330JABAK Specifications

Manufacturer Part Number 5AK330JABAK Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) - Lead Spacing 0.197" (5.00mm) Lead Spacing Straight		
Category Capacitors Package Radial, Disc Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Manufacturer Part Number	5AK330JABAK
Package Radial, Disc Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Category	Capacitors
Series - Capacitance 33pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight		Ceramic Capacitors
Capacitance 33pF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Package	Radial, Disc
Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -30°C ~ 85°C Features - Case General Purpose Failure Rate - Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) - Case General (Max) - Case	Series	-
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.197" Dia (5.00mm)Height - Seated (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Capacitance	33pF
Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style COG, NPO -30°C ~ 85°C - General Purpose - Failure Rate - 0 General Purpose Radial, Disc Radial, Disc 0.197" Dia (5.00mm) - Lead Spacing 0.197" (4.00mm) Straight	Tolerance	±5%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Straight -30°C ~ 85°C -30°C ~	Voltage - Rated	100V
Features - Cartings -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Applications	General Purpose
Package / Case Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm)	Failure Rate	-
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.157" (4.00mm) - 0.197" (5.00mm) Straight	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.197" (5.00mm) Lead Style Straight	Size / Dimension	0.197" Dia (5.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.157" (4.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

5AK330JABAK Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5AK330JABAK Payment Methods



















5AK330JABAK Shipping Methods













If you have any question about 5AK330JABAK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com