



5GU270JEECANM Information



For Reference Only

Part Number 5GU270JEECANM Manufacturer AVX Corporation Category

Capacitors

Ceramic Capacitors

Description CAP CER 27PF 4KV N750 RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5GU270JEECANM Specifications

Manufacturer Part Number 5GU270JEECANM Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 27pF Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight		
Category Capacitors Package Radial, Disc Series - Capacitance 27pF Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Manufacturer Part Number	5GU270JEECANM
Package Radial, Disc Series - Capacitance 27pF Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 27pF Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Category	Capacitors
Series - Capacitance 27pF Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight		Ceramic Capacitors
Capacitance 27pF Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Package	Radial, Disc
Tolerance ±5% Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features - Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) - Case (Max) Lead Spacing 0.236" (6.00mm) Lead Style 1800 - Straight	Series	-
Voltage - Rated 4000V (4kV) Temperature Coefficient N750 Operating Temperature -30°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Capacitance	27pF
Temperature Coefficient Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight N750 - General Purpose - General Purpose - General Purpose - General Purpose - Ocentry 1940 - Company - Com	Tolerance	±5%
Operating Temperature -30°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Voltage - Rated	4000V (4kV)
Features - Cartes - C	Temperature Coefficient	N750
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Operating Temperature	-30°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Applications	General Purpose
Package / Case Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm)	Failure Rate	-
Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.236" (6.00mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.157" (4.00mm) - Under the seated (Max) Straight 0.236" (6.00mm)	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.236" (6.00mm) Lead Style Straight	Size / Dimension	0.315" Dia (8.00mm)
Lead Spacing0.236" (6.00mm)Lead StyleStraight	Height - Seated (Max)	0.157" (4.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.236" (6.00mm)
Report errors?	Lead Style	Straight
		Report errors?

5GU270JEECANM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5GU270JEECANM Payment Methods



















5GU270JEECANM Shipping Methods













If you have any question about 5GU270JEECANM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com