



5MQ101KAAAD Information



For Reference Only

Part Number 5MQ101KAAAD
Manufacturer AVX Corporation
Category Capacitors

y Capacitors
Ceramic Capacitors

Description CAP CER 100PF 500V Y5U RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5MQ101KAAAD Specifications

Manufacturer Part Number 5MQ101KAAAD Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 100pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight		
Category Capacitors Package Radial, Disc Series - Capacitance 100pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Manufacturer Part Number	5MQ101KAAAD
Package Radial, Disc Series - Capacitance 100pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 100pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Category	Capacitors
Series - Capacitance 100pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight		Ceramic Capacitors
Capacitance 100pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Package	Radial, Disc
Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5U (E) Operating Temperature -30°C ~ 85°C Features - Case General Purpose Failure Rate - Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Case Straight	Series	-
Voltage - Rated500VTemperature CoefficientY5U (E)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Capacitance	100pF
Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Y5U (E) -30°C ~ 85°C -30°C ~ 85°C -4 -4 -4 -4 -4 -4 -4 -4 -4 -4 -4 -4 -4	Tolerance	±10%
Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Voltage - Rated	500V
Features - General Purpose - General Purpose - General Purpose - Through Hole - Through Hole - Radial, Disc - Radial, Disc - Size / Dimension - Disc (Max) - Disc (Max) - Lead Spacing - Case Straight - Seated (Max) - Straight - Seated Straight - Straight - Straight - Seated Straight - Straight - Seated Straight - Straight - Seated Straig	Temperature Coefficient	Y5U (E)
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.118" (3.00mm) - 0.197" (5.00mm) Straight	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.197" (5.00mm) Lead Style Straight	Size / Dimension	0.157" Dia (4.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.118" (3.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

5MQ101KAAAD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5MQ101KAAAD Payment Methods





















5MQ101KAAAD Shipping Methods













If you have any question about 5MQ101KAAAD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com