

5NLE2450E

5NLE2450E Information

Heisener.com	Part Number Manufacturer Category Description Package	5NLE2450E Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses FUSE CRTRDGE 450A 5.5KVAC NONSTD Cartridge, Non-Standard For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5NLE2450E Specifications

Manufacturer Part NumberSNLE2450EManufacturerLitelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-ApplicationsIndicatingFeaturesIndicatingClassEApprovals-Operating Temperature-Operating Temperature80kAMounting TypeHolderStace / CaseCartridge, Non-StandardStace / CaseCartridge, No		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartidge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartidgeCurrent Rating450AVoltage Rating - AC5500V (5.5KV)Voltage Rating - DC-ApplicationsTansformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature0Approvals-ApprovalsBiolAOperating Temperature0Automing Type0Stack (Case)Stack (Case)Fackage / CaseCartidge, Non-StandardSize / Dimension1787s" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Manufacturer Part Number	5NLE2450E
FirstElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Applications-Applications-FeaturesIndicatingApprovals-Operating Temperature-Apacking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.785" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.7875" L x 3.000" W x 6.380" H (454.03mm x 76.0mm x 162.05mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse Type450AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage04AMounting TypeHolderPackage / CaseCartridge NameSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard
Current Rating 450A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartidge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Series	POWR-GARD?
Voltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1,875" L x 3,000" W x 6,380" H (454,03mm x 76,20mm x 162,00mm x 16	Current Rating	450A
Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Voltage Rating - AC	5500V (5.5kV)
ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Voltage Rating - DC	-
FractionIndicatingFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Response Time	-
ClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Applications	Transformer Protection
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Class	E
Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Approvals	-
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Descrit	Size / Dimension	17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)
Report error		Report errors?

5NLE2450E Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 5NLE2450E, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com