



### **5NLE30E Information**

Heisener.com

Part Number 5NLE30E
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 30A 5.5KVAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **5NLE30E Specifications**

Manufacturer Part Number5NLE30EManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 17.875" L (76.20mm x 454.03mm)Report errors?		
CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Manufacturer Part Number	5NLE30E
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Category	Circuit Protection
Series         POWR-GARD?           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         5500V (5.5kV)           Voltage Rating - DC         -           Response Time         -           Applications         Transformer Protection           Features         Indicating           Class         E           Approvals         -           Operating Temperature         -           Breaking Capacity @ Rated Voltage         80kA           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         3.000" Dia x 17.875" L (76.20mm x 454.03mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 30A  Voltage Rating - AC 5500V (5.5kV)  Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E  Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 30A  5500V (5.5kV)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC S500V (5.5kV)  Voltage Rating - DC	Series	POWR-GARD?
Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Transformer Protection  Features  Indicating  Class  E  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  5500V (5.5kV)  -  6500V (5.5kV)  -  6600V (5600V (56	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Applications  Transformer Protection  Features  Indicating  Class  E  Approvals  - Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  - Cautidge, Non-Standard  3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Current Rating	30A
Response Time - Applications Transformer Protection  Features Indicating  Class E  Approvals -  Operating Temperature -  Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Voltage Rating - AC	5500V (5.5kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Transformer Protection Indicating E All Cartridge, Non-Standard 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Voltage Rating - DC	-
Features Indicating  Class E  Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Applications	Transformer Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  80kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Class	E
Breaking Capacity @ Rated Voltage 80kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 17.875" L (76.20mm x 454.03mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	3.000" Dia x 17.875" L (76.20mm x 454.03mm)
		Report errors?

#### **5NLE30E Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **5NLE30E Payment Methods**





















### **5NLE30E Shipping Methods**













If you have any question about 5NLE30E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com