



5NR471MOBLM Information



For Reference Only

Part Number 5NR471MOBLM
Manufacturer AVX Corporation
Category Capacitors

egory Capacitors
Ceramic Capacitors

Description CAP CER 470PF 1KV Y5V RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









5NR471MOBLM Specifications

Manufacturer Part Number 5NR471MOBLM Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 470pF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Spacing Formed Leads - Kinked		
Category Capacitors Package Radial, Disc Series - Capacitance 470pF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Manufacturer Part Number	5NR471MOBLM
Package Radial, Disc Series - Capacitance 470pF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 470pF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Category	Capacitors
Series - Capacitance 470pF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance 470pF Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Package	Radial, Disc
Tolerance ±20% Voltage - Rated 1000V (1kV) Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Series	-
Voltage - Rated Temperature Coefficient Y5F Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 1000V (1kV) 1000	Capacitance	470pF
Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Y5F -30°C ~ 85°C - Refine Rate - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0	Tolerance	±20%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Son	Voltage - Rated	1000V (1kV)
Features - General Purpose - General Purpose - Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) - Lead Spacing 0.197" (5.00mm) Formed Leads - Kinked	Temperature Coefficient	Y5F
Ratings - General Purpose Failure Rate - Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Applications	General Purpose
Package / Case Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm)	Failure Rate	-
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing 0.157" (4.00mm) - Lead Spacing 0.197" (5.00mm) Formed Leads - Kinked	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.197" (5.00mm) Lead Style Formed Leads - Kinked	Size / Dimension	0.197" Dia (5.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.157" (4.00mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

5NR471MOBLM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

5NR471MOBLM Payment Methods





















5NR471MOBLM Shipping Methods













If you have any question about 5NR471MOBLM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com