

5NS101KAACI

Request a Quote

5NS101KAACI Information

Www.heisener.com		5NS101KAACI AVX Corporation Capacitors Ceramic Capacitors
	Description	CAP CER 100PF 2KV Y5V RADIAL
	Package	Radial, Disc
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5NS101KAACI Specifications

Manufacturer Part Number SNS101KAACI Manufacturer AVX Corporation Category Capacitors Catagory Caramic Capacitors Package Radial, Disc Series - Capacitance 100pF Tolerance 100yF Voltage - Rated 2000V (2kV) Temperature Coefficient SysSov (2kV) Operating Temperature -30°C ~ 8°C Operating Temperature -30°C ~ 8°C Applications General Purpose Faiture Rate - Mounting Type Intrody Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm)	_	
CategoryCapacitorsPackageRadial, DiscPackageRadial, DiscSeries-Capacitance100pFTolerance±10%Voltage - Rated2000V (2kV)Temperature CoefficientY5FOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Manufacturer Part Number	5NS101KAACI
Indext Ceramic CapacitorsPackageRadial, DiscSeries-Capacitance100pFTolerance±10%Voltage - Rated2000V (2kV)Temperature CoefficientY5FOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSeneral PurposeSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Manufacturer	AVX Corporation
PackageRdial, DiscSeries-Capacitance100pFTolerance±10%Voltage - Rated2000V (2kV)Temperature CoefficientY5FOperating Temperature-30°C ~ 85°CFeatures-ApplicationsGeneralPurposeFailure Rate-Mounting TypeSing HolePackage / CaseRadia, DiscSize / Dimension0.157° Dia (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197° (5.00mm)Lead StyleStraightStraightStraight	Category	Capacitors
Series-Capacitance100pFTolerance±10%Voltage - Rated2000V (2kV)Temperature CoefficientSysOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight		Ceramic Capacitors
Capacitance100pFTolerance±10%Voltage - Rated2000V (2kV)Temperature CoefficientV5FOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeMouge AllelSize / DimensionN18° (300m)Height - Seated (Max)0.118° (300m)Thickness (Max)-Lead Spacing190° (500mn)Lead StyleStraight	Package	Radial, Disc
Toleance±10%Voltage - Rated2000V (2kV)Temperature CoefficientY5FOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead SpacingDispecingLead StyleStraight	Series	-
Voltage - Rated2000V (2kV)Temperature CoefficientV5FOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeMillelPackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Thickness (Max)0.197" (5.00mm)Lead SpacingSize JoinensionLead SpacingSize JoinensionHeight - Seated (Max)Size JoinensionStated Stated Sta	Capacitance	100pF
Temperature CoefficientY5FOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStright	Tolerance	±10%
Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Voltage - Rated	2000V (2kV)
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Temperature Coefficient	Y5F
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Operating Temperature	-30°C ~ 85°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Mounting Type	Through Hole
Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Size / Dimension	0.157" Dia (4.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.118" (3.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

5NS101KAACI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

5NS101KAACI Payment Methods



5NS101KAACI Shipping Methods



If you have any question about 5NS101KAACI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com