



50Q102KXCAA Information



For Reference Only

Part Number 5OQ102KXCAA
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 1000PF 500V Y5P RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50Q102KXCAA Specifications

Manufacturer Part Number 50Q102KXCAA Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 1000pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236° Dia (6.00mm) Height - Seated (Max) 0.157° (4.00mm) Thickness (Max) -		
Category Capacitors Package Radial, Disc Series - Capacitance 1000pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Manufacturer Part Number	5OQ102KXCAA
Package Radial, Disc Series - Capacitance 1000pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Manufacturer	AVX Corporation
PackageRadial, DiscSeries-Capacitance1000pFTolerance±10%Voltage - Rated500VTemperature CoefficientY5P (B)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.236" Dia (6.00mm)Height - Seated (Max)0.157" (4.00mm)	Category	Capacitors
Series - Capacitance 1000pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)		Ceramic Capacitors
Capacitance 1000pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Package	Radial, Disc
Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Series	-
Voltage - Rated Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) 500V 75P (B) 600 600 75P (B) 600 75P (B) 600 75P (B) 600 75P (4.00mm) 600 75P (4.00mm)	Capacitance	1000pF
Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Y5P (B) Y5P (B) Y5P (B) Ago (B) Ago (C) Ratings - Through Hole Radial, Disc 0.236" Dia (6.00mm) 0.157" (4.00mm)	Tolerance	±10%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Voltage - Rated	500V
Features - Case	Temperature Coefficient	Y5P (B)
Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.236" Dia (6.00mm)Height - Seated (Max)0.157" (4.00mm)	Failure Rate	-
Size / Dimension 0.236" Dia (6.00mm) Height - Seated (Max) 0.157" (4.00mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.157" (4.00mm)	Package / Case	Radial, Disc
	Size / Dimension	0.236" Dia (6.00mm)
Thickness (Max) -	Height - Seated (Max)	0.157" (4.00mm)
	Thickness (Max)	-
Lead Spacing 0.236" (6.00mm)	Lead Spacing	0.236" (6.00mm)
Lead Style Formed Leads - Kinked	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

50Q102KXCAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50Q102KXCAA Payment Methods



















50Q102KXCAA Shipping Methods













If you have any question about 5OQ102KXCAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com