



50Q181KAAAA Information



For Reference Only

Part Number 5OQ181KAAAA
Manufacturer AVX Corporation
Category Capacitors

Capacitors
Ceramic Capacitors

Description CAP CER 180PF 500V Y5P RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50Q181KAAAA Specifications

Manufacturer Part Number 50Q181KAAAA Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 180pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight		
Category Capacitors Package Radial, Disc Series - Capacitance 180pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Manufacturer Part Number	5OQ181KAAAA
Package Radial, Disc Series - Capacitance 180pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 180pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Category	Capacitors
Series - Capacitance 180pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight		Ceramic Capacitors
Capacitance 180pF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Package	Radial, Disc
Tolerance ±10% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Case General Purpose Failure Rate - Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Case Straight	Series	-
Voltage - Rated500VTemperature CoefficientY5P (B)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Capacitance	180pF
Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Y5P (B) Y5P (B) Y5P (B) Y5P (B) Y5P (B) Applications (Auore Associated	Tolerance	±10%
Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Voltage - Rated	500V
Features - Cartings -	Temperature Coefficient	Y5P (B)
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Ratings	-
Mounting Type Package / Case Radial, Disc Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.118" (3.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.118" (3.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.118" (3.00mm) - 0.197" (5.00mm) Straight	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.197" (5.00mm) Lead Style Straight	Size / Dimension	0.157" Dia (4.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.118" (3.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

50Q181KAAAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50Q181KAAAA Payment Methods





















50Q181KAAAA Shipping Methods













If you have any question about 5OQ181KAAAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com