



50Q222MOEAM Information



For Reference Only

Part Number 5OQ222MOEAM
Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 2200PF 500V Y5P RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









50Q222MOEAM Specifications

Manufacturer Part Number 50Q222M0EAM Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 2200pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)		
Category Capacitors Ceramic Capacitors Package Radial, Disc Series - Capacitance 2200pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Size / Dimension Capacitors Capacitors Radial, Disc Capacitors Ceramic Capacitors Capacitors - Capacitors	Manufacturer Part Number	5OQ222MOEAM
Package Radial, Disc Series - Capacitance 2200pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Manufacturer	AVX Corporation
PackageRadial, DiscSeries-Capacitance2200pFTolerance±20%Voltage - Rated500VTemperature CoefficientY5P (B)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)	Category	Capacitors
Series - Capacitance 2200pF Tolerance ±20% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)		Ceramic Capacitors
Capacitance $2200 pF$ Tolerance $\pm 20\%$ Voltage - Rated $500 V$ Temperature Coefficient $Y5P (B)$ Operating Temperature $-30^{\circ}C \sim 85^{\circ}C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension 0.315° Dia $(8.00 mm)$	Package	Radial, Disc
Tolerance ±20% Voltage - Rated 500V Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Series	-
Voltage - Rated Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Size / Dimension 500V 75P (B) -30°C ~ 85°C - Through Hole Ratings - Ratings - One and Purpose Through Hole Radial, Disc Radial, Disc 0.315" Dia (8.00mm)	Capacitance	2200pF
Temperature Coefficient Y5P (B) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Y5P (B) Y5P (B) Y5P (B) Y5P (B) Through Hole Agree (Base) Radial, Disc Output Disc Output Output Disc Disc Output Disc Disc Output Disc Disc Disc Output Disc	Tolerance	±20%
Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension -30°C ~ 85°C - Through Hole - 0.315" Dia (8.00mm)	Voltage - Rated	500V
Features - Case	Temperature Coefficient	Y5P (B)
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Operating Temperature	-30°C ~ 85°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Applications	General Purpose
Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm)	Failure Rate	-
Size / Dimension 0.315" Dia (8.00mm)	Mounting Type	Through Hole
	Package / Case	Radial, Disc
	Size / Dimension	0.315" Dia (8.00mm)
Height - Seated (Max) 0.157" (4.00mm)	Height - Seated (Max)	0.157" (4.00mm)
Thickness (Max) -	Thickness (Max)	-
Lead Spacing 0.197" (5.00mm)	Lead Spacing	0.197" (5.00mm)
Lead Style Formed Leads - Kinked	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

50Q222MOEAM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

50Q222M0EAM Payment Methods



















50Q222MOEAM Shipping Methods













If you have any question about 5OQ222MOEAM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com