

5TQ103SAFAA

Request a Quote

5TQ103SAFAA Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



5TQ103SAFAA Specifications

Manufacturer Part NumberSTQ 103SAFAAManufacturer Ant NumberAVX CorporationCategoryCapacitorsPackageRadial, DiscSeries-Capacitance1000pFTolerance20%, +50%Voltage - Rated500VTomperature Coefficient50V (P)Opating Temperature-30°C ~ 85°CPatures-30°C ~ 85°CFaitures-30°C ~ 85°CFaitures Ate-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeNorugi HolePackage / CaseRatial, DiscSize / Dimension0.354° Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Ladad Spacing1.97" (5.00mm)Lada SpacingMaring TypeLada SpacingMaring TypeLada SpacingMaring TypeSize / Dimension-Size / Dimension0.197" (5.00mm)Height - Seated (Max)-Lada SpacingMaring TypeLada SpacingMaring TypeLada SpacingMaring TypeLada SpacingMaring TypeLada SpacingMaring TypeLada SpacingStaring TypeLada Spacing <th></th> <th></th>		
CategoryCapacitorsPackageRadial, DiscPackageRadial, DiscSeries-Capacitance10000pFTolerance-20%, +50%Voltage - Rated500VTomperature CoefficientS0V (SOperating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposePailure Rate-Mounting TypeS104Package / CaseRadial, DiscSize / Dimension0.354° Dia (9.00mm)Height - Seated (Max)-Height - Seated (Max)-Lead Spacing0.197° (5.00mm)Lead StyleStrieght	Manufacturer Part Number	5TQ103SAFAA
Indext Ceramic CapacitorsPackageRadial, DiscSeries-Capacitance10000pFTolerance-20%, +50%Voltage - Rated500VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Manufacturer	AVX Corporation
PackageRadial, DiscSeries-Capacitance10000pFTolerance-20%, +50%Voltage - Rated500VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeMought HoleSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Category	Capacitors
Series-Capacitance10000pFTolerance-20%, +50%Voltage - Rated500VTemperature Coefficient95V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeHolog HoleSize / DimensionAidial, DiscSize / Dimension0.197" (5.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight		Ceramic Capacitors
Capacitance10000pFTolerance-20%, +50%Voltage - Rated500VTemperature CoefficientV5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeMoustSize / DimensionS154° Dia (9.00mm)Height - Seated (Max)0.197° (5.00mm)Thickness (Max)-Lead Spacing1.97° (5.00mm)Lead StyleStraight <td>Package</td> <td>Radial, Disc</td>	Package	Radial, Disc
Tolerance-20%, +50%Voltage - Rated500VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / Case0.354" Dia (9.00mm)Size / Dimension0.197" (5.00mm)Height - Seated (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Series	-
Voltage - Rated500VTemperature CoefficientV5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeHolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead SpacingStraightKate StraigStraight<	Capacitance	10000pF
Temperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.197" (5.00mm)Height - Seated (Max)-Thickness (Max)0.197" (5.00mm)Lead SpacingStraight	Tolerance	-20%, +50%
Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Voltage - Rated	500V
Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Temperature Coefficient	Y5V (F)
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)0.197" (5.00mm)Lead SpacingDiagnetKeight - Seated (Max)Straight	Operating Temperature	-30°C ~ 85°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Mounting Type	Through Hole
Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Size / Dimension	0.354" Dia (9.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.197" (5.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

5TQ103SAFAA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

5TQ103SAFAA Payment Methods





If you have any question about 5TQ103SAFAA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com