



### 600L220FT200T Information

ener.com

For Reference Only

Part Number 600L220FT200T

Manufacturer American Technical Ceramics

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 22PF 200V C0G/NP0 0402

Package 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **600L220FT200T Specifications**

Manufacturer Part Number         6001.220FT200T           Manufacturer         American Technical Ceramics           Category         Capacitors           Package         0402 (1005 Metric)           Series         ATC 600L           Capacitance         22pF           Tolerance         ±1%           Voltage - Rated         200V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss, Ultra Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Spacing         -           Report errors 2		
Category         Capacitors           Package         0402 (1005 Metric)           Series         ATC 600L           Capacitance         22pF           Tolerance         ±1%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss, Ultra Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	600L220FT200T
Package         0402 (1005 Metric)           Series         ATC 600L           Capacitance         22pF           Tolerance         ±1%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss, Ultra Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Style         -	Manufacturer	American Technical Ceramics
Package         0402 (1005 Metric)           Series         ATC 600L           Capacitance         22pF           Tolerance         ±1%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss, Ultra Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         ATC 600L           Capacitance         22pF           Tolerance         ±1%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss, Ultra Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         22pF           Tolerance         ±1%           Voltage - Rated         200V           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss, Ultra Low ESR           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.040" L x 0.020" W (1.02mm x 0.51mm)           Height - Seated (Max)         -           Thickness (Max)         0.024" (0.60mm)           Lead Spacing         -           Lead Style         -	Package	0402 (1005 Metric)
Tolerance ±1%  Voltage - Rated 200V  Temperature Coefficient COG, NP0  Operating Temperature -55°C ~ 125°C  Features High Q, Low Loss, Ultra Low ESR  Ratings -	Series	ATC 600L
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low Loss, Ultra Low ESRRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.60mm)Lead Spacing-Lead Style-	Capacitance	22pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low Loss, Ultra Low ESRRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.040" L x 0.020" W (1.02mm x 0.51mm)Height - Seated (Max)-Thickness (Max)0.024" (0.60mm)Lead Spacing-Lead Style-	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features High Q, Low Loss, Ultra Low ESR Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing - Lead Style -	Voltage - Rated	200V
Features High Q, Low Loss, Ultra Low ESR  Ratings - Applications RF, Microwave, High Frequency  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)  Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm)  Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm)  Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss, Ultra Low ESR
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.040" L x 0.020" W (1.02mm x 0.51mm) Height - Seated (Max) - Thickness (Max) 0.024" (0.60mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case       0402 (1005 Metric)         Size / Dimension       0.040" L x 0.020" W (1.02mm x 0.51mm)         Height - Seated (Max)       -         Thickness (Max)       0.024" (0.60mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.040" L x 0.020" W (1.02mm x 0.51mm)         Height - Seated (Max)       -         Thickness (Max)       0.024" (0.60mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.024" (0.60mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.040" L x 0.020" W (1.02mm x 0.51mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.024" (0.60mm)
	Lead Spacing	-
Report errors?	Lead Style	-
Report chois:		Report errors?

#### 600L220FT200T Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **600L220FT200T Payment Methods**



















### 600L220FT200T Shipping Methods













If you have any question about 600L220FT200T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com