

# 6012R-020

#### 6012R-020 Information

Heisener.com	Part Number Manufacturer Category Description Package	6012R-020 API Delevan Inc. Transformers Power Transformers XFRMR LAMINATED 1.1VA THRU HOLE - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 6012R-020 Specifications

Manufacturer API Delevan Inc.   Category Transformers   Power Transformers Power Transformers   Package -   Scries 6012R   Type Laminated Core   Voltage - Primary 115V   Voltage - Secondary (Full Load) Parallel 10V, Series 20V   Current - Output (Max) Parallel 110mA, Series 55mA   Scondary Winding(s) Single   Secondary Winding(s) Dual   Center Tap No   Power - Max 1.1 VA   Mounting Type Through Hole   Size / Dimension 34.93mm L x 28.58mm W   Height - Seated (Max) 23.80mm		
CategoryTransformersPackage-Package-Series6012RTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypePrinary MindieSize / DimensionSecondary La SetsmanSize / DimensionSecondary La SetsmanMouting TypeSecondary MindieSize / DimensionSecondary La Setsman WSize / DimensionSecondary La Setsman WWeightSecondary La Setsman WSets (Max)Secondary La Setsman MSets (Max)<	Manufacturer Part Number	6012R-020
InterfactPower TransformersPackage-Series6012RTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleSize / Dimension34.93mm L x 28.58mm WSize / Dimension23.00mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Manufacturer	API Delevan Inc.
Package-Series6012RTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StyleSecondary Winding(s)Size / Dimension34.93mm Lx 28.58mm WVoltage - Isolation23.00vrmsWeightStory TransWeight0.17 Ib (77.11g)	Category	Transformers
Series6012RTypeLaminated CoreVoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StyleSecondary Winding(s)Size / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)SioWrmsWotage - Isolation500VrmsWeight0.17 lb (77.11g)		Power Transformers
TypeLaminated CoreYoltage - Primary115VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation0.17 lb (77.11g)	Package	-
Voltage - PrimaryInformationVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StyleSecondary Winding(s)Size / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmWoltage - Isolation0.17 lb (77.11g)	Series	6012R
Voltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation0.17 lb (77.11g)	Туре	Laminated Core
Current - Output (Max)Parallel 110mA, Series 55mAPrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.00VrmsVoltage - Isolation0.17 lb (77.11g)	Voltage - Primary	115V
Primary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination Style9C PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation500VrmsWeight0.17 lb (77.11g)	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Current - Output (Max)	Parallel 110mA, Series 55mA
Center TapNoPower - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Primary Winding(s)	Single
Power - Max1.1 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Secondary Winding(s)	Dual
Note HandInterferenceMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Center Tap	No
Termination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)23.80mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Power - Max	1.1 VA
Size / Dimension 34.93mm L x 28.58mm W   Height - Seated (Max) 23.80mm   Voltage - Isolation 2500Vrms   Weight 0.17 lb (77.11g)	Mounting Type	Through Hole
Height - Seated (Max)23.80mmVoltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Termination Style	PC Pin
Voltage - Isolation2500VrmsWeight0.17 lb (77.11g)	Size / Dimension	34.93mm L x 28.58mm W
Weight 0.17 lb (77.11g)	Height - Seated (Max)	23.80mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.17 lb (77.11g)
		Report errors?

#### 6012R-020 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 6012R-020, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com