

## 6014-012 Information

Heisener.com

For Reference Only

**Part Number** 6014-012

Manufacturer API Delevan Inc.

Transformers

Category

**Power Transformers** 

**Description** 

XFRMR LAMINATED 6VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **6014-012 Specifications**

Manufacturer Part Number         6014-012           Manufacturer         API Delevan Inc.           Category         Transformers           Power Transformers         Power Transformers           Package         -           Series         6014           Type         Laminated Core           Voltage - Primary         115V           Voltage - Secondary (Full Load)         Parallel 6.3V, Series 12.6V           Current - Output (Max)         Parallel 1A, Series 500mA           Primary Winding(s)         Single           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         6 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 33.32mm W		
Category  Transformers  Power Transformers  Package  - Series  6014  Type  Laminated Core  Voltage - Primary  115V  Voltage - Secondary (Full Load)  Parallel 6.3V, Series 12.6V  Current - Output (Max)  Parallel 1A, Series 500mA  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style	Manufacturer Part Number	6014-012
Package Series 6014 Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style	Manufacturer	API Delevan Inc.
Package - Go14 Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 1A, Series 500mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin	Category	Transformers
Series 6014 Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 1A, Series 500mA Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 6 VA Mounting Type Through Hole Termination Style PC Pin		Power Transformers
Type  Voltage - Primary  115V  Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Laminated Core  Laminated Core  Laminated Core  No  Parallel 6.3V, Series 12.6V  Parallel 1A, Series 500mA  Parallel 1A, Series 500mA  Parallel 1A, Series 500mA  No  Poul  Through Hole  PC Pin	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 6.3V, Series 12.6V  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  115V  Parallel 6.3V, Series 12.6V  Parallel 1A, Series 500mA  Pinary Winding(s)  Dual  Center Tap  No  Power - Max  Power - Max  Power - Max  Primary Winding(s)  Power - Max  Pow	Series	6014
Voltage - Secondary (Full Load)  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Parallel 6.3V, Series 12.6V  Parallel 1A, Series 500mA  Single  Dual  Population of the series of th	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Termination Style Parallel 1A, Series 500mA Single Dual Character Tap No Power - Max Fundamental Type Through Hole PC Pin	Voltage - Primary	115V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Single  Dual  No  Poul  POP Pin	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)  Center Tap  No  Power - Max  6 VA  Mounting Type  Through Hole  Termination Style  PC Pin	Current - Output (Max)	Parallel 1A, Series 500mA
Center TapNoPower - Max6 VAMounting TypeThrough HoleTermination StylePC Pin	Primary Winding(s)	Single
Power - Max 6 VA  Mounting Type Through Hole  Termination Style PC Pin	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin	Center Tap	No
Termination Style PC Pin	Power - Max	6 VA
·	Mounting Type	Through Hole
Size / Dimension 41.28mm L x 33.32mm W	Termination Style	PC Pin
	Size / Dimension	41.28mm L x 33.32mm W
Height - Seated (Max) 33.32mm	Height - Seated (Max)	33.32mm
Voltage - Isolation 2500Vrms	Voltage - Isolation	2500Vrms
Weight 0.44 lb (199.58g)	Weight	0.44 lb (199.58g)
Report errors?		Report errors?

#### 6014-012 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **6014-012 Payment Methods**





















## **6014-012 Shipping Methods**













If you have any question about 6014-012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com